

**Rail Mounted Terminal Blocks : Polyamide Range Of Terminals : Feed Through Terminal : KUT 2.5**



<b>Type of Connection</b>	MS Screw Clamp
<b>Insulating Material</b>	Polyamide 66
<b>Terminal Pitch</b>	6 mm ( 0.23 Inch)
<b>Terminal Width</b>	42.5 mm ( 1.66 Inch)
<b>Terminal Height</b>	41 mm ( 1.60 Inch)
<b>Rated Cross Section</b>	2.5 sq mm
<b>Wire Stripping Length</b>	10 mm
<b>Screw Size</b>	M3

**Connection Possibility**

<b>Stranded wire</b>	Max : 2.5 sq mm	Min : 0.5 sq mm
<b>Solid wire</b>	Max : 4 sq mm	Min : 0.5 sq mm

<b>Ratings</b>	<b>IEC</b>	<b>UL</b>
Voltage	800 V	600 V
Current	24 A	25 A
Conductor Size	2.5 sq mm	Min : 20 AWG    Max : 12 AWG
Tightening Torque	0.5 Nm	7 LbIn

**Terminal Accessories**

<b>End Plate</b>	KPNS
<b>Partition Plate Without Foot</b>	KBM
<b>Partition Plate With Foot</b>	KBXF
<b>Protection Cover</b>	PCK3
<b>End Clamp</b>	SCUN, SCUSL, SCUDD, SCKN, DCKN
<b>Cross Connection Link Assembly</b>	CCLM2.5K - 2W
<b>Comb-type Shorting Link</b>	SLC4N - 2W
<b>Marking Label</b>	LABEL KN5.5
<b>Group Marking Carrier</b>	SCKNMLH, SCUNMLH, DCKNMLH
<b>Terminal Colours</b>	GREY, KHAKHI, RED, YELLOW, BLUE, BLACK, GREEN
<b>Mounting Channel</b>	CHS10, CHK10, CHS3, CHS5, CHK5, CHK3, CHKS3, CHKS5, CHKS10, CHKDS10, CHKD10