











SPT300

Terminal Type – SPT300, High current connectors with secured hinged cover, nominal voltage: 1000 V AC/1500 V DC, Rated cross-section – 300 mm², nominal current: 520 A, connection method: Bolt connection, number of connections: 2, cross-section: 35 mm² – 300 mm², 4 AWG - 750 KCMIL, mounting type: TS 35/7.5, TS 35/15

Product Accessories

DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	

Fixed Bridge		
CCLASPT300-2W	Width : 35.00 mm Thickness : 3.20 mm Pitch : 55.00 mm Length : 95.00 mm	
CCLASPT300-3W	Width : 35.00 mm Thickness : 3.20 mm Pitch : 55.00 mm Length : 150.00 mm	
Marker For Terminal Blocks		
LABEL KN12	Width : 12.00 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
GMH 20	Height : 51.00 mm Width : 20.00 mm Length : 41.50 mm	
GMH10	Height : 51.00 mm Width : 10.00 mm Length : 41.50 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	