











PQ2.5-1C1P



Terminal Type - PQ2.5-1C1P , Feed-through terminal block, nominal voltage: 500V, nominal current: 24 A, connection method: Push-in connection / plug connection, number of connections: 2, cross section: 0.08 mm² - 4 mm², AWG : 24-12 , mounting type: TS 35/7.5, TS 35/15

Product Accessories



DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	

End Clamp		
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
CSP2.5	Height : 22.70 mm Width : 2.00 mm Length : 50.70 mm	
Marker For Terminal Blocks		
LABEL KN5	Width : 5.00 mm	
Partition Plate		
DBF-1	Height : 31.40 mm Width : 3.00 mm Length : 60.00 mm	
Plug-in Bridge/Jumper		
SLPU5-2W	Height : 26.00 mm Width : 9.15 mm Pitch : 5.00 mm	
SLPU5-3W	Height : 26.00 mm Width : 14.15 mm Pitch : 5.00 mm	
SLPU5-10W	Height : 26.00 mm Width : 49.15 mm Pitch : 5.00 mm	
SLPU5-4W	Height : 26.00 mm Width : 19.15 mm Pitch : 5.00 mm	

Plug-in Bridge/Jumper		
SLPU5-5W	Height : 26.00 mm Width : 24.15 mm Pitch : 5.00 mm	
SLPU5-6W	Height : 26.00 mm Width : 29.15 mm Pitch : 5.00 mm	
SLPU5-7W	Height : 26.00 mm Width : 34.15 mm Pitch : 5.00 mm	

Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	

PLUG		
PQPP2.5-F-10W	Height : 42.00 mm Width : 15.80 mm Pitch : 5.00 mm Length : 50.00 mm	
PQPP2.5-F-12W	Height : 42.00 mm Width : 15.80 mm Pitch : 5.00 mm Length : 60.00 mm	
PQPP2.5-F-14W	Height : 42.00 mm Width : 15.80 mm Pitch : 5.00 mm Length : 70.00 mm	
PQPP2.5-F-15W	Height : 42.00 mm Width : 15.80 mm Pitch : 5.00 mm Length : 75.00 mm	

PLUG		
PQPP2.5-F-2W	Height : 42.00 mm Width : 15.80 mm Pitch : 5.00 mm Length : 10.00 mm	
PQPP2.5-F-3W	Height : 42.00 mm Width : 15.80 mm Pitch : 5.00 mm Length : 15.00 mm	
PQPP2.5-F-4W	Height : 42.00 mm Width : 15.80 mm Pitch : 5.00 mm Length : 20.00 mm	
PQPP2.5-F-5W	Height : 42.00 mm Width : 15.80 mm Pitch : 5.00 mm Length : 25.00 mm	
PQPP2.5-F-6W	Height : 42.00 mm Width : 15.80 mm Pitch : 5.00 mm Length : 30.00 mm	
PQPP2.5-F-8W	Height : 42.00 mm Width : 15.80 mm Pitch : 5.00 mm Length : 40.00 mm	
Operating lever		
PQPP2.5F-LVR-1W-ORG	Height : 29.70 mm Thickness : 9.00 mm	
PQPP2.5F-LVR-2W-ORG	Height : 29.70 mm Thickness : 9.80 mm	