

## CATDM4

Terminal Type - CATDM4 , Test Disconnect Terminal Block , Connection method: Bolt connection, nominal voltage: 1100 V, nominal current: 41 A, connection method: Bolt connection, number of connections: 2, Rated cross section: 6 mm<sup>2</sup>, cross section: 2.5 mm<sup>2</sup> - 6 mm<sup>2</sup> , mounting type: TS32

### Product Accessories

Cover Profile		
PCD 39	Height : 26.00 mm Thickness : 1.50 mm Length : 70.00 mm	
PCD26	Height : 26.00 mm Thickness : 1.50 mm Length : 70.00 mm	
PCD3	Height : 26.20 mm Width : 73.00 mm Thickness : 1.50 mm	
DIN Rail Perforated		
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
End Clamp		
SCS	Height : 26.90 mm Length : 21.00 mm	
SCSN	Height : 31.00 mm Width : 8.40 mm Length : 27.00 mm	
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	

<b>End Clamp</b>		
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
<b>End Cover</b>		
EPD4	Height : 44.20 mm Width : 2.50 mm Length : 69.00 mm	
<b>Insertion Bridge</b>		
ADSL-2W	Width : 20.50 mm Pitch : 13.00 mm Length : 24.00 mm	
ADSL-10W	Width : 124.50 mm Pitch : 13.00 mm Length : 24.00 mm	
ADSL-3W	Width : 33.50 mm Pitch : 13.00 mm Length : 24.00 mm	
ADSL-4W	Width : 46.50 mm Pitch : 13.00 mm Length : 24.00 mm	
ADSL-7W	Width : 85.50 mm Pitch : 13.00 mm Length : 24.00 mm	
<b>Marker For Terminal Blocks</b>		
LABEL KN5.5	Height : 2.42 mm Width : 6.00 mm Length : 7.50 mm	
<b>Marker carriers</b>		
GMC	Height : 48.00 mm Width : 39.00 mm Thickness : 1.00 mm Length : 38.00 mm	
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	

<b>Marker carriers</b>		
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	

