







CBTM5

Terminal Type - CBTM5, Feed Through Terminal Block, nominal voltage: 1100 V, nominal current: 76 A , Rated cross-section - 16 mm², connection method: Bolt Connection - Nut driver operated , number of connections: 2, cross section: 2.5 mm² - 16 mm², mounting type :TS32

Product Accessories

Cover Profile		
PCC3NV	Width : 300.00 mm Thickness : 1.50 mm Length : 48.50 mm	
PCCM30NV	Width : 30.00 mm Thickness : 1.00 mm Length : 45.50 mm	
PCCM45K	Height : 13.15 mm Width : 45.00 mm Thickness : 1.30 mm	
DIN Rail Perforated		
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
End Clamp		
SCS	Height : 26.90 mm Length : 21.00 mm	
SCSN	Height : 31.00 mm Width : 8.40 mm Length : 27.00 mm	
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	

End Clamp		
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
EPS4NV	Height : 28.50 mm Width : 2.50 mm Length : 46.00 mm	
Insertion Bridge		
KSL5-10W	Width : 142.50 mm Pitch : 15.00 mm Length : 26.50 mm	
KSL5-2W	Width : 37.50 mm Pitch : 15.00 mm Length : 26.00 mm	
KSL5-3W	Width : 22.50 mm Pitch : 15.00 mm Length : 26.00 mm	
KSL5-4W	Width : 52.50 mm Pitch : 15.00 mm Length : 26.00 mm	
KSL5-5W	Width : 67.50 mm Pitch : 15.00 mm Length : 26.00 mm	
Marker For Terminal Blocks		
LABEL KN6.5	Width : 6.70 mm	
Partition Plate		
KBZF	Height : 65.00 mm Width : 1.50 mm Length : 65.00 mm	
Marker carriers		
GMC	Height : 48.00 mm Width : 39.00 mm Thickness : 1.00 mm Length : 38.00 mm	

Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	