








CSLT1

Terminal Type - CSLT1, Feed Through Terminal block, nominal voltage: 800 V, nominal current: 57 A, Rated cross-section - 10 mm², connection method: Screw connection with spring support, number of connections: 2, cross-section: 1.5 mm² - 10 mm², mounting type: TS32

Product Accessories

Cover Profile		
PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
Cover Profile Carrier		
UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
DIN Rail Perforated		
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
End Clamp		
SCS	Height : 26.90 mm Length : 21.00 mm	
SCSN	Height : 31.00 mm Width : 8.40 mm Length : 27.00 mm	
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	

End Cover		
EPSL	Height : 44.00 mm Width : 2.50 mm Length : 50.00 mm	
Fixed Bridge		
CCLA1L-10W	Height : 28.00 mm Pitch : 11.00 mm Length : 106.60 mm	
CCLA1L-2W	Height : 28.00 mm Pitch : 11.00 mm Length : 20.20 mm	
CCLA1L-3W	Height : 28.00 mm Pitch : 11.00 mm Length : 30.20 mm	
CCLA1L-4W	Height : 28.00 mm Pitch : 11.00 mm Length : 40.20 mm	
CCLA1L-5W	Height : 28.00 mm Pitch : 11.00 mm Length : 51.20 mm	
Marker For Terminal Blocks		
LABEL KN10	Width : 10.00 mm	
Partition Plate		
KBZF	Height : 65.00 mm Width : 1.50 mm Length : 65.00 mm	
Switching Jumper		
RSL1L	Width : 7.00 mm Thickness : 1.60 mm Length : 18.00 mm	
LSR1L	Height : 30.00 mm Width : 6.00 mm	

Marker carriers		
GMC	Height : 48.00 mm Width : 39.00 mm Thickness : 1.00 mm Length : 38.00 mm	
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	