










CST2.5

Terminal Type - CST2.5, Feed Through Terminal block, nominal voltage: 800 V, nominal current: 32 A, Rated cross-section - 4.0 mm², connection method: Screw connection, number of connections: 2, cross-section: 0.5 mm² - 6 mm², mounting type: TS32

Product Accessories

Cover Profile		
PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
Cover Profile Carrier		
UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
DIN Rail Perforated		
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
End Clamp		
SCS	Height : 26.90 mm Length : 21.00 mm	
SCSN	Height : 31.00 mm Width : 8.40 mm Length : 27.00 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
EPX	Height : 48.60 mm Width : 2.00 mm Length : 39.60 mm	

Fixed Bridge		
CCLA2.5-10W	Height : 24.12 mm Width : 5.00 mm Pitch : 6.75 mm Length : 66.00 mm	
CCLA2.5-3W	Height : 24.12 mm Width : 5.00 mm Pitch : 6.75 mm Length : 18.85 mm	
CCLA2.5-4W	Height : 24.12 mm Width : 5.00 mm Pitch : 6.75 mm Length : 25.60 mm	
CCLA2.5-5W	Height : 24.12 mm Width : 5.00 mm Pitch : 6.75 mm Length : 32.35 mm	
CCLA2.5-6W	Height : 24.12 mm Width : 5.00 mm Pitch : 6.75 mm Length : 39.00 mm	
CCLA2.5-8W	Height : 24.12 mm Width : 5.00 mm Pitch : 6.75 mm Length : 52.60 mm	
CCLA2.5-2W	Height : 24.12 mm Width : 5.00 mm Pitch : 6.75 mm Length : 12.10 mm	
Insertion Bridge		
SLC2.5-2W	Height : 26.00 mm Width : 3.00 mm Pitch : 6.70 mm Length : 12.50 mm	
SLC2.5-10W	Height : 26.00 mm Width : 3.00 mm Pitch : 6.70 mm Length : 66.10 mm	
SLC2.5-4W	Height : 26.00 mm Width : 3.00 mm Pitch : 6.70 mm Length : 25.90 mm	
SLC2.5-5W	Height : 26.00 mm Width : 3.00 mm Pitch : 6.70 mm Length : 32.60 mm	

Insertion Bridge		
SLC2.5-3W	Height : 26.00 mm Width : 3.00 mm Pitch : 6.70 mm Length : 19.20 mm	
Marker For Terminal Blocks		
LABEL KN6.5	Width : 6.70 mm	
Partition Plate		
BPX	Height : 60.00 mm Width : 3.00 mm Length : 55.00 mm	
KBXF	Height : 53.40 mm Width : 1.50 mm Length : 54.00 mm	
Switching Jumper		
LSR2.5-6	Height : 23.00 mm Width : 5.00 mm	
RSL2.5	Thickness : 1.20 mm Pitch : 6.60 mm Length : 12.60 mm	
Warning Label		
WL4	Height : 25.20 mm Thickness : 1.10 mm Length : 28.80 mm	
Marker carriers		
GMC	Height : 48.00 mm Width : 39.00 mm Thickness : 1.00 mm Length : 38.00 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	