

## **DPBB50CN**

Terminal Type - DPBB50CN , High current connectors , nominal voltage: 1000 V, nominal current: 150 A, connection method : Bolt connection with clinch nut , number of connections: 2, cross section: 10 mm<sup>2</sup> - 50 mm<sup>2</sup>, AWG: 6 - 1 , mounting type: TS 35/7.5, TS 35/15 , TS 32

### Product Accessories

<b>Cover Profile</b>		
PCP120	Width : 41.00 mm Thickness : 1.50 mm Length : 126.00 mm	
<b>DIN Rail Perforated</b>		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
<b>DIN Rail, Unperforated</b>		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
<b>End Cap</b>		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
<b>End Clamp</b>		
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	

<b>End Clamp</b>		
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
<b>Marker For Terminal Blocks</b>		
LABEL KN10	Height : 2.89 mm Width : 10.00 mm Length : 8.50 mm	
<b>Partition Plate</b>		
BPN70	Height : 67.50 mm Width : 3.00 mm Length : 123.80 mm	
<b>Marker carriers</b>		
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	