

DPBB70

Terminal Type - DPBB70, High current connectors, nominal voltage: 1000 V, nominal current: 192 A, Rated cross-section - 70 mm², connection method: Bolt connection, number of connections: 2, cross-section: 10 mm² - 70 mm², AWG: 6 - 2/0, mounting type: TS 35/7.5, TS 35/15, TS 32

Product Accessories


Cover Profile

PCP120	Width : 41.00 mm Thickness : 1.50 mm Length : 126.00 mm	
--------	---	---


DIN Rail Perforated

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	



DIN Rail, Unperforated

CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

End Cap

CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
-----------	---	---


End Clamp

SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	


Marker For Terminal Blocks

LABEL KN10	Height : 2.89 mm Width : 10.00 mm Length : 8.50 mm	
------------	--	---

Partition Plate

BPN70	Height : 67.50 mm Width : 3.00 mm Length : 125.00 mm	
-------	--	---

Marker carriers

SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	

