

## DST35

Terminal Type - DST35 , Feed-through terminal block, nominal voltage: 1000 V, nominal current: 125 A, Rated cross-section – 35 mm<sup>2</sup>, connection method: Spring Cage connection, number of connections: 2, cross section: 6 mm<sup>2</sup> - 35 mm<sup>2</sup>, mounting type: TS 35/7.5, TS 35/15

### Product Accessories

| DIN Rail Perforated    |  |   |
|------------------------|--|---|
| CHKDS                  | Height : 15.00 mm<br>Width : 35.00 mm<br>Thickness : 1.50 mm<br>Length : 2,000.00 mm |    |
| CHKS                   | Height : 7.50 mm<br>Width : 35.00 mm<br>Thickness : 1.00 mm                          |    |
| DIN Rail, Unperforated |  |   |
| CHKD                   | Height : 15.00 mm<br>Width : 35.00 mm<br>Thickness : 1.50 mm                         |   |
| CHK                    | Height : 7.50 mm<br>Width : 35.00 mm<br>Thickness : 1.00 mm                          |  |
| End Cap                |  |   |
| CHKENDCAP              | Height : 14.00 mm<br>Width : 9.00 mm<br>Length : 41.50 mm                            |  |
| End Clamp              |  |   |
| SCUP                   | Height : 34.00 mm<br>Width : 9.00 mm<br>Length : 44.75 mm                            |  |
| SCEC35                 | Height : 31.50 mm<br>Width : 8.00 mm<br>Length : 45.80 mm                            |  |
| SCUSL                  | Height : 41.10 mm<br>Width : 8.00 mm<br>Length : 47.50 mm                            |  |
| SCUDD                  | Height : 50.00 mm<br>Width : 10.00 mm<br>Length : 55.60 mm                           |  |

| End Clamp |  |   |
|-----------|--|---|
| DCKN      | Height : 33.00 mm<br>Width : 6.00 mm<br>Length : 43.50 mm  |  |
| DCKN10    | Height : 35.00 mm<br>Width : 10.00 mm<br>Length : 43.50 mm |  |
| SCKN      | Height : 34.50 mm<br>Width : 8.00 mm<br>Length : 44.90 mm  |  |
| SCUN      | Height : 35.50 mm<br>Width : 9.50 mm<br>Length : 50.60 mm  |  |

| Marker For Terminal Blocks |  |  |
|----------------------------|--|--|
| LABEL KN12                 | Height : 2.43 mm<br>Width : 12.00 mm<br>Length : 8.50 mm |  |

| Plug-in Bridge/Jumper |  |   |
|-----------------------|--|---|
| SSL35                 | Height : 43.00 mm<br>Width : 13.00 mm<br>Length : 11.30 mm |  |

| Marker carriers |  |   |
|-----------------|--|---|
| SCUDDMLH        | Height : 71.50 mm<br>Width : 11.00 mm<br>Length : 55.60 mm |  |
| SCUNMLH         | Height : 53.50 mm<br>Width : 11.00 mm<br>Length : 50.60 mm |  |
| DCKNMLH         | Height : 45.00 mm<br>Width : 10.00 mm<br>Length : 43.50 mm |  |
| SCKNMLH         | Height : 42.00 mm<br>Width : 16.00 mm<br>Length : 44.70 mm |  |