KUDF4

Terminal Type - KUDF4, Fuse terminal block, nominal voltage: 800 V, nominal current: 6.3 A, suitable size of cartridge fuse : 5X20 mm and 5X25 mm, connection method: Screw connection, number of connections: 2, Rated cross section - 4 mm², cross section: 0.5 mm² - 4 mm², AWG: 20-12, mounting type: TS 35/7.5, TS 35/15 , TS 32

Product Accessories

Cover Profile		
PCPDBF-3	Height : 14.10 mm Thickness : 1.50 mm Length : 79.00 mm	
DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	

End Clamp		
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
Insertion Bridge		
UFSL-10W	Height : 22.50 mm Width : 2.60 mm Pitch : 8.20 mm Length : 79.50 mm	
UFSL-3W	Height : 22.50 mm Width : 2.60 mm Pitch : 8.20 mm Length : 22.10 mm	
UFSL-4W	Height : 22.50 mm Width : 2.60 mm Pitch : 8.20 mm Length : 30.30 mm	
UFSL-5W	Height : 22.50 mm Width : 2.60 mm Pitch : 8.20 mm Length : 38.50 mm	

Insertion Bridge		
UFSL-2W	Height : 22.50 mm Width : 2.60 mm Pitch : 8.20 mm Length : 13.90 mm	
Marker For Terminal Blocks		
LABEL KN5.5	Height : 2.42 mm Width : 6.00 mm Length : 7.50 mm	
LABEL KN8	Height : 2.43 mm Width : 8.00 mm Length : 8.50 mm	
Partition Plate		
DBF-3	Height : 50.00 mm Width : 3.00 mm Length : 78.00 mm	
KBZF	Height : 65.00 mm Width : 1.50 mm Length : 65.00 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	