





















## KUDT4-2X2

Terminal Type - KUDT4-2X2, Knife disconnect terminal block, nominal voltage: 800 V, nominal current: 20 A, Rated cross-section: 4.0 mm<sup>2</sup>, connection method: Screw connection, number of connections: 4, cross-section: 0.5 mm<sup>2</sup> - 4 mm<sup>2</sup>, mounting type: TS 35/7.5, TS 35/15

### Product Accessories

| DIN Rail Perforated    |                                                                                      |                                                                                       |
|------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| CHKDS                  | Height : 15.00 mm<br>Width : 35.00 mm<br>Thickness : 1.50 mm<br>Length : 2,000.00 mm |    |
| CHKS                   | Height : 7.50 mm<br>Width : 35.00 mm<br>Thickness : 1.00 mm                          |    |
| CHS                    | Height : 15.00 mm<br>Width : 32.00 mm<br>Thickness : 1.50 mm                         |    |
| DIN Rail, Unperforated |                                                                                      |                                                                                       |
| CHKD                   | Height : 15.00 mm<br>Width : 35.00 mm<br>Thickness : 1.50 mm                         |  |
| CHK                    | Height : 7.50 mm<br>Width : 35.00 mm<br>Thickness : 1.00 mm                          |  |
| End Cap                |                                                                                      |                                                                                       |
| CHKENDCAP              | Height : 14.00 mm<br>Width : 9.00 mm<br>Length : 41.50 mm                            |  |
| End Clamp              |                                                                                      |                                                                                       |
| SCUP                   | Height : 34.00 mm<br>Length : 44.75 mm                                               |  |
| SCUSL                  | Height : 41.10 mm<br>Width : 8.00 mm<br>Length : 47.50 mm                            |  |
| SCUDD                  | Height : 50.00 mm<br>Width : 10.00 mm<br>Length : 55.60 mm                           |  |

| End Clamp        |                                                            |  |                                                                                       |
|------------------|------------------------------------------------------------|--|---------------------------------------------------------------------------------------|
| DCKN             | Height : 33.00 mm<br>Width : 6.00 mm<br>Length : 43.50 mm  |  |    |
| DCKN10           | Height : 35.00 mm<br>Width : 10.00 mm<br>Length : 43.50 mm |  |    |
| SCKN             | Height : 34.50 mm<br>Width : 8.00 mm<br>Length : 44.90 mm  |  |    |
| SCUN             | Height : 35.50 mm<br>Width : 9.50 mm<br>Length : 50.60 mm  |  |    |
| End Cover        |                                                            |  |                                                                                       |
| KPMD4            | Height : 42.40 mm<br>Width : 1.50 mm<br>Length : 67.00 mm  |  |   |
| Insertion Bridge |                                                            |  |                                                                                       |
| SLC4N-10W        | Width : 58.60 mm<br>Pitch : 6.00 mm<br>Length : 23.00 mm   |  |  |
| SLC4N-3W         | Width : 16.65 mm<br>Pitch : 6.00 mm<br>Length : 23.00 mm   |  |  |
| SLC4N-4W         | Width : 22.65 mm<br>Pitch : 6.00 mm<br>Length : 23.00 mm   |  |  |
| SLC4N-5W         | Width : 28.65 mm<br>Pitch : 6.00 mm<br>Length : 23.00 mm   |  |  |
| SLC4N-6W         | Width : 34.60 mm<br>Pitch : 6.00 mm<br>Length : 23.00 mm   |  |  |
| SLC4N-2W         | Width : 10.91 mm<br>Pitch : 6.00 mm<br>Length : 23.00 mm   |  |  |

| Marker For Terminal Blocks |                                                            |                                                                                       |
|----------------------------|------------------------------------------------------------|---------------------------------------------------------------------------------------|
| LABEL KN5.5                | Width : 6.00 mm                                            |    |
| Partition Plate            |                                                            |                                                                                       |
| KNBF 2.5/10                | Height : 58.00 mm<br>Width : 1.50 mm<br>Length : 55.50 mm  |    |
| Marker carriers            |                                                            |                                                                                       |
| SCUDDMLH                   | Height : 71.50 mm<br>Width : 10.00 mm<br>Length : 55.60 mm |    |
| SCUNMLH                    | Height : 53.50 mm<br>Width : 9.50 mm<br>Length : 50.60 mm  |   |
| DCKNMLH                    | Height : 45.50 mm<br>Width : 6.00 mm<br>Length : 43.50 mm  |  |
| SCKNMLH                    | Height : 45.50 mm<br>Width : 8.00 mm<br>Length : 44.90 mm  |  |