


## **KUT2.5N**



Terminal Type - KUT2.5N , Feed-through terminal block for photo voltaic applications, nominal voltage: 1000 V, nominal current : 24 A , Rated Cross-section : 2.5mm<sup>2</sup>, connection method: Screw connection, number of connections: 2, cross section: 0.5 mm<sup>2</sup> - 4 mm<sup>2</sup>, AWG: 20 - 12, mounting type: TS 35/7.5, TS 35/15 , TS 32











### Product Accessories


Cover Profile		
PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
Cover Profile Carrier		
UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	


End Clamp		
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	

End Cover		
KPXN	Height : 41.50 mm Width : 1.50 mm Length : 41.50 mm	

Fixed Bridge		
CCLM2.5N-2W	Height : 20.00 mm Width : 5.00 mm Pitch : 5.00 mm Length : 9.80 mm	
CCLM2.5N-10W	Height : 20.00 mm Width : 5.00 mm Pitch : 5.00 mm Length : 49.80 mm	

<b>Fixed Bridge</b>		
CCLM2.5N-3W	Height : 20.00 mm Width : 5.00 mm Pitch : 5.00 mm Length : 14.80 mm	
CCLM2.5N-4W	Height : 20.00 mm Width : 5.00 mm Pitch : 5.00 mm Length : 19.80 mm	
CCLM2.5N-5W	Height : 20.00 mm Width : 5.00 mm Pitch : 5.00 mm Length : 24.80 mm	
<b>Insertion Bridge</b>		
SLC2.5N-2W	Width : 9.60 mm Pitch : 5.00 mm Length : 23.00 mm	
SLC2.5N-10W	Width : 49.20 mm Pitch : 5.00 mm Length : 23.00 mm	
SLC2.5N-3W	Width : 14.60 mm Pitch : 5.00 mm Length : 23.00 mm	
SLC2.5N-4W	Width : 19.60 mm Pitch : 5.00 mm Length : 23.00 mm	
SLC2.5N-5W	Width : 24.60 mm Pitch : 5.00 mm Length : 23.00 mm	
<b>Marker For Terminal Blocks</b>		
LABEL KN5	Height : 2.42 mm Width : 5.00 mm Length : 7.50 mm	
<b>Partition Plate</b>		
KNBF 2.5/10	Height : 58.00 mm Width : 1.50 mm Length : 55.50 mm	

Switching Jumper		
LSR2.5N		
RSL2.5N		

Warning Label		
WL2.5N	Height : 24.00 mm Thickness : 1.10 mm Length : 24.00 mm	

Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	