

## KUT35

Terminal Type - KUT35 , Feed-through terminal block, nominal voltage: 1000 V, nominal current: 125 A, connection method: Screw connection, number of connections: 2, Rated cross section: 35 mm<sup>2</sup>, cross section: 10 mm<sup>2</sup> - 35 mm<sup>2</sup>, AWG: 1-14, mounting type: TS35/7.5 , TS35/15 , and TS32

### Product Accessories

Cover Profile		
PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
Cover Profile Carrier		
UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	

<b>End Clamp</b>		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
<b>Fixed Bridge</b>		
CCLA35K-2W	Height : 27.00 mm Pitch : 17.00 mm Length : 25.50 mm	
CCLA35K-10W	Height : 27.00 mm Pitch : 17.00 mm Length : 165.00 mm	
CCLA35K-3W	Height : 27.00 mm Pitch : 17.00 mm Length : 42.50 mm	

<b>Fixed Bridge</b>		
CCLA35K-4W	Height : 27.00 mm Pitch : 17.00 mm Length : 60.00 mm	
CCLA35K-5W	Height : 27.00 mm Pitch : 17.00 mm Length : 77.50 mm	
<b>Marker For Terminal Blocks</b>		
LABEL KN17	Width : 17.00 mm	
<b>Partition Plate</b>		
KBZF	Height : 65.00 mm Width : 1.50 mm Length : 65.00 mm	
<b>Switching Jumper</b>		
LSR35K	Height : 29.50 mm Width : 6.50 mm	
RSL35K	Thickness : 1.60 mm Pitch : 17.00 mm Length : 26.70 mm	
<b>Warning Label</b>		
WL35	Width : 35.00 mm Thickness : 1.50 mm Length : 74.00 mm	
<b>Marker carriers</b>		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm	

**Marker carriers**

SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	
---------	---	---

