












## KUT4





Terminal Type - KUT4 , Feed-through terminal block, nominal voltage: 800 V, nominal current: 32 A, Tested at - 1100 V, connection method: Screw connection, number of connections: 2, Rated cross section: 4.0 mm<sup>2</sup> , cross section: 0.5 mm<sup>2</sup> - 6 mm<sup>2</sup>, AWG: 20 - 10, mounting type: TS35/7.5 , TS35/15 , TS32 and TS15



### Product Accessories

| Cover Profile          |                                                                                      |                                                                                       |
|------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| PCPDBF-4               | Height : 13.10 mm<br>Thickness : 1.00 mm<br>Length : 95.00 mm                        |    |
| PCK3                   | Height : 28.00 mm<br>Width : 58.35 mm<br>Thickness : 1.00 mm                         |    |
| Cover Profile Carrier  |                                                                                      |                                                                                       |
| UHDD                   | Height : 74.50 mm<br>Thickness : 2.00 mm<br>Length : 55.82 mm                        |   |
| DIN Rail Perforated    |                                                                                      |                                                                                       |
| CHM                    | Height : 5.00 mm<br>Width : 15.00 mm<br>Thickness : 1.00 mm                          |  |
| CHS                    | Height : 15.00 mm<br>Width : 32.00 mm<br>Thickness : 1.50 mm                         |  |
| CHKDS                  | Height : 15.00 mm<br>Width : 35.00 mm<br>Thickness : 1.50 mm<br>Length : 2,000.00 mm |  |
| CHKS                   | Height : 7.50 mm<br>Width : 35.00 mm<br>Thickness : 1.00 mm                          |  |
| DIN Rail, Unperforated |                                                                                      |                                                                                       |
| CHKD                   | Height : 15.00 mm<br>Width : 35.00 mm<br>Thickness : 1.50 mm                         |  |
| CHK                    | Height : 7.50 mm<br>Width : 35.00 mm<br>Thickness : 1.00 mm                          |  |

| End Cap   |                                                               |                                                                                       |
|-----------|---------------------------------------------------------------|---------------------------------------------------------------------------------------|
| CHKENDCAP | Height : 14.00 mm<br>Width : 9.00 mm<br>Length : 41.50 mm     |    |
| End Clamp |                                                               |                                                                                       |
| SCUP      | Height : 34.00 mm<br>Length : 44.75 mm                        |    |
| SCEC35    | Height : 31.50 mm<br>Width : 8.00 mm<br>Length : 45.80 mm     |    |
| SCUSL     | Height : 41.10 mm<br>Width : 8.00 mm<br>Length : 47.50 mm     |    |
| SCUDD     | Height : 50.00 mm<br>Width : 10.00 mm<br>Length : 55.60 mm    |   |
| DCKN      | Height : 33.00 mm<br>Width : 6.00 mm<br>Length : 43.50 mm     |  |
| DCKN10    | Height : 35.00 mm<br>Width : 10.00 mm<br>Length : 43.50 mm    |  |
| SCKN      | Height : 34.50 mm<br>Width : 8.00 mm<br>Length : 44.90 mm     |  |
| SCUN      | Height : 35.50 mm<br>Width : 9.50 mm<br>Length : 50.60 mm     |  |
| End Cover |                                                               |                                                                                       |
| KPX       | Height : 36.00 mm<br>Thickness : 1.50 mm<br>Length : 40.00 mm |  |

| Fixed Bridge     |                                                           |                                                                                       |
|------------------|-----------------------------------------------------------|---------------------------------------------------------------------------------------|
| CCLA2.5-10W      | Height : 20.00 mm<br>Pitch : 6.75 mm<br>Length : 66.10 mm |    |
| CCLA2.5-3W       | Height : 20.00 mm<br>Pitch : 6.75 mm<br>Length : 18.70 mm |    |
| CCLA2.5-4W       | Height : 20.00 mm<br>Pitch : 6.75 mm<br>Length : 25.60 mm |    |
| CCLA2.5-5W       | Height : 20.00 mm<br>Pitch : 6.75 mm<br>Length : 32.35 mm |    |
| CCLA2.5-6W       | Height : 20.00 mm<br>Pitch : 6.75 mm<br>Length : 39.00 mm |   |
| CCLA2.5-8W       | Height : 20.00 mm<br>Pitch : 6.75 mm<br>Length : 52.60 mm |  |
| CCLA2.5-2W       | Height : 20.00 mm<br>Pitch : 6.75 mm<br>Length : 11.90 mm |  |
| Insertion Bridge |                                                           |                                                                                       |
| SLC2.5-2W        | Width : 12.50 mm<br>Pitch : 6.70 mm<br>Length : 26.00 mm  |  |
| SLC2.5-10W       | Width : 65.10 mm<br>Pitch : 6.70 mm<br>Length : 25.00 mm  |  |
| SLC2.5-4W        | Width : 24.90 mm<br>Pitch : 6.70 mm<br>Length : 25.00 mm  |  |
| SLC2.5-5W        | Width : 31.60 mm<br>Pitch : 6.70 mm<br>Length : 25.00 mm  |  |

|                                   |                                                               |                                                                                       |
|-----------------------------------|---------------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>Marker For Terminal Blocks</b> |                                                               |                                                                                       |
| LABEL KN6.5                       | Width : 6.70 mm                                               |    |
| <b>Partition Plate</b>            |                                                               |                                                                                       |
| KBXF                              | Height : 53.40 mm<br>Thickness : 1.50 mm<br>Length : 54.00 mm |    |
| KBX                               | Height : 43.00 mm<br>Thickness : 1.50 mm<br>Length : 54.00 mm |    |
| <b>Spacer Plate</b>               |                                                               |                                                                                       |
| SBN1                              | Height : 12.10 mm<br>Width : 1.37 mm<br>Length : 13.20 mm     |    |
| <b>Switching Jumper</b>           |                                                               |                                                                                       |
| LSR2.5-6                          | Height : 23.00 mm<br>Width : 5.00 mm                          |  |
| RSL2.5                            | Thickness : 1.20 mm<br>Pitch : 6.60 mm<br>Length : 12.60 mm   |  |
| <b>Warning Label</b>              |                                                               |                                                                                       |
| WL4                               | Height : 25.20 mm<br>Thickness : 1.10 mm<br>Length : 28.80 mm |  |
| <b>Marker carriers</b>            |                                                               |                                                                                       |
| SCUDDMLH                          | Height : 71.50 mm<br>Width : 10.00 mm<br>Length : 55.60 mm    |  |
| SCUNMLH                           | Height : 53.50 mm<br>Width : 9.50 mm<br>Length : 50.60 mm     |  |
| GMH10                             | Height : 51.00 mm<br>Width : 10.00 mm<br>Length : 41.50 mm    |  |

| Marker carriers |                                                            |                                                                                     |
|-----------------|------------------------------------------------------------|-------------------------------------------------------------------------------------|
| GMH 20          | Height : 51.00 mm<br>Width : 20.00 mm<br>Length : 41.50 mm |  |
| DCKNMLH         | Height : 45.50 mm<br>Width : 6.00 mm<br>Length : 43.50 mm  |  |
| SCKNMLH         | Height : 45.50 mm<br>Width : 8.00 mm<br>Length : 44.90 mm  |  |

