




## KUT4

Terminal Type - KUT4 , Feed-through terminal block, nominal voltage: 800 V, nominal current: 32 A, Tested at - 1100 V, connection method: Screw connection, number of connections: 2, Rated cross section: 4.0 mm<sup>2</sup> , cross section: 0.5 mm<sup>2</sup> - 6 mm<sup>2</sup>, AWG: 20 - 10, mounting type: TS35/7.5 , TS35/15 , TS32 and TS15

### Product Accessories

Cover Profile		
PCPDBF-4	Height : 13.10 mm Thickness : 1.00 mm Length : 95.00 mm	
PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
Cover Profile Carrier		
UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
DIN Rail Perforated		
CHM	Height : 5.00 mm Width : 15.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

<b>End Cap</b>		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
<b>End Clamp</b>		
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
<b>End Cover</b>		
KPX	Height : 36.00 mm Width : 1.50 mm Length : 40.00 mm	

<b>Fixed Bridge</b>		
CCLA2.5-10W	Height : 24.12 mm Width : 5.00 mm Pitch : 6.75 mm Length : 66.00 mm	
CCLA2.5-3W	Height : 24.12 mm Width : 5.00 mm Pitch : 6.75 mm Length : 18.85 mm	
CCLA2.5-4W	Height : 24.12 mm Width : 5.00 mm Pitch : 6.75 mm Length : 25.60 mm	
CCLA2.5-5W	Height : 24.12 mm Width : 5.00 mm Pitch : 6.75 mm Length : 32.35 mm	
CCLA2.5-6W	Height : 24.12 mm Width : 5.00 mm Pitch : 6.75 mm Length : 39.00 mm	
CCLA2.5-8W	Height : 24.12 mm Width : 5.00 mm Pitch : 6.75 mm Length : 52.60 mm	
CCLA2.5-2W	Height : 24.12 mm Width : 5.00 mm Pitch : 6.75 mm Length : 12.10 mm	
<b>Insertion Bridge</b>		
SLC2.5-2W	Height : 26.00 mm Width : 3.00 mm Pitch : 6.70 mm Length : 12.50 mm	
SLC2.5-10W	Height : 26.00 mm Width : 3.00 mm Pitch : 6.70 mm Length : 66.10 mm	
SLC2.5-4W	Height : 26.00 mm Width : 3.00 mm Pitch : 6.70 mm Length : 25.90 mm	
SLC2.5-5W	Height : 26.00 mm Width : 3.00 mm Pitch : 6.70 mm Length : 32.60 mm	

Marker For Terminal Blocks		
LABEL KN6.5	Width : 6.70 mm	
Partition Plate		
KBXF	Height : 53.40 mm Width : 1.50 mm Length : 54.00 mm	
KBX	Height : 43.00 mm Width : 1.50 mm Length : 54.00 mm	
Spacer Plate		
SBN1	Height : 12.10 mm Width : 1.37 mm Length : 15.50 mm	
Switching Jumper		
LSR2.5-6	Height : 23.00 mm Width : 5.00 mm	
RSL2.5	Thickness : 1.20 mm Pitch : 6.60 mm Length : 12.60 mm	
Warning Label		
WL4	Height : 25.20 mm Thickness : 1.10 mm Length : 28.80 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
GMH10	Height : 51.00 mm Width : 10.00 mm Length : 42.25 mm	

Marker carriers		
GMH20	Height : 51.00 mm Width : 20.00 mm Length : 42.25 mm	
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	

