


KUT6N

Terminal Type - KUT6N, Feed-through terminal block for photo voltaic applications, nominal voltage: 1000 V, nominal current: 41 A, connection method: Screw connection, number of connections: 2, cross section: 0.5 mm² - 10 mm², AWG: 20 - 8 , mounting type: TS 35/7.5, TS 35/15 , TS 32

Product Accessories


Cover Profile

PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
------	--	---

Cover Profile Carrier

UHDD	Height : 74.50 mm Width : 2.00 mm Length : 55.82 mm	
------	---	---


DIN Rail Perforated







CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	







DIN Rail, Unperforated




CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

End Cap

CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
-----------	---	---

End Clamp		
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
KPXN	Height : 41.50 mm Width : 1.50 mm Length : 41.50 mm	
Fixed Bridge		
CCLA6N-2W	Height : 20.50 mm Width : 6.30 mm Pitch : 8.05 mm Length : 14.40 mm	
CCLA6N-10W	Height : 20.50 mm Width : 6.30 mm Pitch : 8.05 mm Length : 78.75 mm	

Fixed Bridge		
CCLA6N-3W	Height : 20.50 mm Width : 6.30 mm Pitch : 8.05 mm Length : 22.40 mm	
CCLA6N-4W	Height : 20.50 mm Width : 6.30 mm Pitch : 8.05 mm Length : 30.50 mm	
CCLA6N-5W	Height : 20.50 mm Width : 6.30 mm Pitch : 8.05 mm Length : 38.50 mm	
CCLA6N-6W	Height : 20.50 mm Width : 6.30 mm Pitch : 8.05 mm Length : 46.50 mm	
Insertion Bridge		
SLC6-10W	Height : 26.00 mm Width : 3.00 mm Pitch : 8.00 mm Length : 78.60 mm	
SLC6-3W	Height : 26.00 mm Width : 3.00 mm Pitch : 8.00 mm Length : 22.60 mm	
SLC6-4W	Height : 26.00 mm Width : 3.00 mm Pitch : 8.00 mm Length : 30.60 mm	
SLC6-5W	Height : 26.00 mm Width : 3.00 mm Pitch : 8.00 mm Length : 38.60 mm	
SLC6-6W	Height : 26.00 mm Width : 3.00 mm Pitch : 8.00 mm Length : 46.60 mm	
SLC6-2W	Height : 26.00 mm Width : 3.00 mm Pitch : 8.00 mm Length : 14.60 mm	
Marker For Terminal Blocks		
LABEL KN8	Height : 2.43 mm Width : 8.00 mm Length : 8.50 mm	

Partition Plate		
KNBF 2.5/10	Height : 58.00 mm Width : 1.50 mm Length : 55.50 mm	
Switching Jumper		
LSR6N	Height : 22.20 mm Width : 5.00 mm	
RSL6N		
Warning Label		
WL6	Height : 28.00 mm Thickness : 1.10 mm Length : 31.00 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	