

LPT335

Terminal Type - LPT335 , Feed-through terminal block, nominal voltage: 400 V, nominal current: 125 A, connection method: Screw connection, Operated by - 4 mm Allen key, number of connections: 4, Rated Cross section: 35 mm² , cross section: 6 mm² - 35 mm², mounting type: TS 35/7.5, TS 35/15 , TS 32

Product Accessories

| Cover Profile | | |
|------------------------|--|---|
| PCK3 | Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm |  |
| Cover Profile Carrier | | |
| UHDD | Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm |  |
| DIN Rail Perforated | | |
| CHKDS | Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm |  |
| CHKS | Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm |  |
| CHS | Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm |  |
| DIN Rail, Unperforated | | |
| CHKD | Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm |  |
| CHK | Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm |  |
| End Cap | | |
| CHKENDCAP | Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm |  |

Marker For Terminal Blocks

| | | |
|------------|--|---|
| LABEL KN12 | Height : 2.43 mm Width : 12.00 mm Length : 8.50 mm |  |
|------------|--|---|

