












OAT10DTS

Terminal Type - OAT10DTS, Test Disconnect terminal block, nominal voltage: 1000 V, nominal current: 57 A, Rated cross-section - 10 mm² connection method: Bolt connection, number of connections: 2, cross-section: 0.5 mm² - 10 mm², mounting type: TS 35/7.5, TS 35/15, TS 32




Product Accessories

DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	

End Clamp		
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
OEP10DTS	Height : 43.50 mm Width : 2.00 mm Length : 95.00 mm	
Insertion Bridge		
OSL10R(4+1)AW	Height : 29.20 mm Width : 3.50 mm Pitch : 13.00 mm Length : 98.00 mm	
Marker For Terminal Blocks		
LABEL KN12	Height : 2.43 mm Width : 12.00 mm Length : 8.50 mm	
Partition Plate		
DBF-5	Height : 54.00 mm Width : 3.00 mm Length : 112.00 mm	
Switching Jumper		
OSLD10-2W	Height : 27.50 mm Width : 23.50 mm Pitch : 13.00 mm	

Switching Jumper		
OSLD10-3W	Height : 27.50 mm Width : 36.50 mm Pitch : 13.00 mm	
OSLD10-4W	Height : 27.50 mm Width : 49.50 mm Pitch : 13.00 mm	

Test Adapter / Test Socket		
OAT6DTSTP-B	Height : 41.70 mm Width : 6.00 mm	
OAT6DTSTP-BL	Height : 41.70 mm Width : 6.00 mm	
OAT6DTSTP-G	Height : 41.70 mm Width : 6.00 mm	
OAT6DTSTP-GR	Height : 41.70 mm Width : 6.00 mm	
OAT6DTSTP-R	Height : 41.70 mm Width : 6.00 mm	
OAT6DTSTP-Y	Height : 41.00 mm Width : 6.00 mm	

Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm	

Marker carriers

SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	
---------	--	---

