

## OAT6T

Terminal Type - OAT6T , Disconnect terminal block, nominal voltage: 800 V (Tested at 1100 V), nominal current: 41 A, Rated cross-section - 6 mm<sup>2</sup>, connection method: Bolt Connection, number of connections: 2, cross-section: 0.5 mm<sup>2</sup> - 6 mm<sup>2</sup>, mounting type: TS 35/7.5, TS 35/15, TS 32

### Product Accessories

Cover Profile		
PCPDBF-4	Height : 13.10 mm Thickness : 1.00 mm Length : 95.00 mm	
DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	

<b>End Clamp</b>		
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
<b>End Cover</b>		
OEP6T	Height : 41.50 mm Thickness : 1.50 mm Length : 69.00 mm	
<b>Insertion Bridge</b>		
OSL6-2W	Width : 17.50 mm Pitch : 11.00 mm Length : 25.50 mm	
OSL6-10W	Width : 105.50 mm Pitch : 11.00 mm Length : 25.50 mm	
OSL6-3W	Width : 28.50 mm Pitch : 11.00 mm Length : 25.50 mm	

Insertion Bridge		
OSL6-4W	Width : 39.50 mm Pitch : 11.00 mm Length : 25.50 mm	
OSL6-5W	Width : 50.50 mm Pitch : 11.00 mm Length : 25.50 mm	
OSL6R-10W	Height : 25.30 mm Width : 105.50 mm Pitch : 11.00 mm	
OSL6R-2W	Height : 25.30 mm Width : 17.50 mm Pitch : 11.00 mm	
OSL6R-3W	Height : 25.30 mm Width : 28.50 mm Pitch : 11.00 mm	
OSL6R-4W	Height : 25.30 mm Width : 3.70 mm Pitch : 11.00 mm Length : 39.50 mm	
OSL6R-5W	Height : 25.30 mm Width : 50.50 mm Pitch : 11.00 mm	
Marker For Terminal Blocks		
LABEL KN 9	Width : 9.00 mm	
Partition Plate		
DBF-4	Height : 54.00 mm Width : 3.00 mm Length : 90.00 mm	
KBZF	Height : 65.00 mm Width : 1.50 mm Length : 65.00 mm	

Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	

