
















ONTM3-6C

Terminal Type - ONTM3-6C , Feed Through Terminal Block , nominal voltage: 1000 V, nominal current: 41 A, connection method : Bolt Connection - Screw and Nut driver operated, number of connections: 2, Rated Cross-section : 6 mm² , cross section: 0.5 mm² - 6 mm², mounting type: TS 35/7.5, TS 35/15 , TS 32

Product Accessories

DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	

End Clamp		
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
ONTEP	Height : 22.80 mm Width : 2.00 mm Length : 47.80 mm	
Fixed Bridge		
CCLAONT9-2W	Height : 18.30 mm Width : 4.80 mm Pitch : 9.00 mm Length : 13.80 mm	
CCLAONT9-10W	Height : 18.30 mm Width : 4.80 mm Pitch : 9.00 mm Length : 85.20 mm	
CCLAONT9-3W	Height : 18.30 mm Width : 4.80 mm Pitch : 9.00 mm Length : 22.80 mm	
CCLAONT9-4W	Height : 18.30 mm Width : 4.80 mm Pitch : 9.00 mm Length : 31.20 mm	
CCLAONT9-5W	Height : 18.30 mm Width : 4.80 mm Pitch : 9.00 mm Length : 40.80 mm	

Marker For Terminal Blocks		
ONTML9	Height : 2.42 mm Width : 9.00 mm Length : 11.50 mm	
Partition Plate		
KBXF	Height : 53.40 mm Width : 1.50 mm Length : 54.00 mm	
Marker carriers		
GMH20	Height : 51.00 mm Width : 20.00 mm Length : 42.25 mm	
GMH10	Height : 51.00 mm Width : 10.00 mm Length : 42.25 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	