












# *PQ2.5-2X2*



Terminal Type - PQ2.5-2X2, Multi conductor Feed-through terminal block, nominal voltage: 1000 V, nominal current: 24 A, Rated cross section: 2.5 mm², connection method: Push-in connection, number of connections: 4, cross section: 0.2 mm² - 4 mm², AWG : 24-12, mounting type: TS 35/7.5, TS 35/15

## Product Accessories

| | | |
|---|---|---|
| **Cover Profile** | | |
| PCPDBF-3 | Height : 14.10 mm<br>Thickness : 1.50 mm<br>Length : 79.00 mm |  |
| **DIN Rail Perforated** | | |
| CHKDS | Height : 15.00 mm<br>Width : 35.00 mm<br>Thickness : 1.50 mm<br>Length : 2,000.00 mm |  |
| CHKS | Height : 7.50 mm<br>Width : 35.00 mm<br>Thickness : 1.00 mm |  |
| **DIN Rail, Unperforated** | | |
| CHKD | Height : 15.00 mm<br>Width : 35.00 mm<br>Thickness : 1.50 mm |  |
| CHK | Height : 7.50 mm<br>Width : 35.00 mm<br>Thickness : 1.00 mm |  |
| **End Cap** | | |
| CHKENDCAP | Height : 14.00 mm<br>Width : 9.00 mm<br>Length : 41.50 mm |  |
| **End Clamp** | | |
| SCUP | Height : 34.00 mm<br>Width : 9.00 mm<br>Length : 44.75 mm |  |
| SCEC35 | Height : 31.50 mm<br>Width : 8.00 mm<br>Length : 45.80 mm |  |

| | | |
|---|---|---|
| **End Clamp** | | |
| SCUSL | Height : 41.10 mm<br>Width : 8.00 mm<br>Length : 47.50 mm |  |
| SCUDD | Height : 50.00 mm<br>Width : 10.00 mm<br>Length : 55.60 mm |  |
| DCKN | Height : 33.00 mm<br>Width : 6.00 mm<br>Length : 43.50 mm |  |
| DCKN10 | Height : 35.00 mm<br>Width : 10.00 mm<br>Length : 43.50 mm |  |
| SCKN | Height : 34.50 mm<br>Width : 8.00 mm<br>Length : 44.90 mm |  |
| SCUN | Height : 35.50 mm<br>Width : 9.50 mm<br>Length : 50.60 mm |  |
| **End Cover** | | |
| CSP2.5-2X2 | Height : 22.70 mm<br>Width : 2.00 mm<br>Length : 74.70 mm |  |
| **Marker For Terminal Blocks** | | |
| LABEL KN5 | Height : 2.42 mm<br>Width : 5.00 mm<br>Length : 7.50 mm |  |
| **Partition Plate** | | |
| DBF-3 | Height : 50.00 mm<br>Width : 3.00 mm<br>Length : 78.00 mm |  |
| **Plug-in Bridge/Jumper** | | |
| SLPU5-2W | Height : 26.00 mm<br>Width : 3.00 mm<br>Pitch : 5.00 mm<br>Length : 9.15 mm |  |

| **Plug-in Bridge/Jumper** | | |
|---|---|---|
| SLPU5-3W | Height : 26.00 mm<br>Width : 3.00 mm<br>Pitch : 5.00 mm<br>Length : 14.15 mm |  |
| SLPU5-10W | Height : 26.00 mm<br>Width : 3.00 mm<br>Pitch : 5.00 mm<br>Length : 49.15 mm |  |
| SLPU5-4W | Height : 26.00 mm<br>Width : 3.00 mm<br>Pitch : 5.00 mm<br>Length : 19.15 mm |  |
| SLPU5-5W | Height : 26.00 mm<br>Width : 3.00 mm<br>Pitch : 5.00 mm<br>Length : 24.15 mm |  |
| SLPU5-6W | Height : 26.00 mm<br>Width : 3.00 mm<br>Pitch : 5.00 mm<br>Length : 29.15 mm |  |
| SLPU5-7W | Height : 26.00 mm<br>Width : 3.00 mm<br>Pitch : 5.00 mm<br>Length : 34.15 mm |  |
| SLPU5-8W | Height : 26.00 mm<br>Width : 3.00 mm<br>Pitch : 5.00 mm<br>Length : 39.15 mm |  |
| SLPU5-9W | Height : 26.00 mm<br>Width : 3.00 mm<br>Pitch : 5.00 mm<br>Length : 44.15 mm |  |

| **Marker carriers** | | |
|---|---|---|
| SCUDDMLH | Height : 71.50 mm<br>Width : 11.00 mm<br>Length : 55.60 mm |  |
| SCUNMLH | Height : 53.50 mm<br>Width : 11.00 mm<br>Length : 50.60 mm |  |
| DCKNMLH | Height : 45.00 mm<br>Width : 10.00 mm<br>Length : 43.50 mm |  |

| **Marker carriers** | | |
|---|---|---|
| SCKNMLH | Height : 42.00 mm<br>Width : 16.00 mm<br>Length : 44.70 mm |  |