








PQD6




Terminal Type - PQD6 , Knife Disconnect Terminal Blocks , nominal voltage: 1000 V, nominal current: 30 A, Rated Cross section - 6 mm², connection method: Push in type, number of connections: 2, cross-section: 0.2 mm² - 10 mm², AWG : 24-8 , mounting type: TS 35/7.5, TS 35/15.

Product Accessories

Cover Profile		
PCP120	Width : 41.00 mm Thickness : 1.50 mm Length : 126.00 mm	
DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	

End Clamp		
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
CSPD6	Height : 42.00 mm Thickness : 2.00 mm Length : 105.00 mm	
Marker For Terminal Blocks		
LABEL KN8	Width : 8.00 mm	
Partition Plate		
BPN70	Height : 67.50 mm Width : 3.00 mm Length : 125.00 mm	
Plug-in Bridge/Jumper		
SLPU8-2W	Height : 33.30 mm Width : 15.20 mm Pitch : 8.00 mm	

Plug-in Bridge/Jumper		
SLPU8-10W	Height : 33.30 mm Width : 79.20 mm Pitch : 8.00 mm	
SLPU8-3W	Height : 33.30 mm Width : 23.20 mm Pitch : 8.00 mm	
SLPU8-4W	Height : 33.30 mm Width : 31.20 mm Pitch : 8.00 mm	
SLPU8-5W	Height : 33.30 mm Width : 39.20 mm Pitch : 8.00 mm	
SLPU8-6W	Height : 33.30 mm Width : 2.50 mm Pitch : 8.00 mm Length : 47.20 mm	
SLPU8-3AW	Height : 33.30 mm Width : 2.50 mm Pitch : 16.00 mm Length : 23.20 mm	
SLPU8-7AW	Height : 33.30 mm Width : 2.50 mm Pitch : 16.00 mm Length : 55.20 mm	
Switching Jumper		
SJD6BIM (2W, 3W, 4W)	Height : 47.25 mm Width : 24.70 mm Length : 31.70 mm	
Test Adapter / Test Socket		
ADP6-YELLOW	Height : 51.80 mm Width : 6.40 mm Length : 6.70 mm	
ADP6-BLACK	Height : 51.80 mm Width : 6.40 mm Length : 6.70 mm	
ADP6-BLUE	Height : 51.80 mm Width : 6.40 mm Length : 6.70 mm	

Test Adapter / Test Socket			
ADP6-RED	Height : 51.80 mm Width : 6.40 mm Length : 6.70 mm		
Marker carriers			
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm		
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm		
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm		
Switching Lock			
SLPQD6	Height : 13.77 mm Width : 7.80 mm Length : 13.32 mm		
JSLPQD6	Height : 13.60 mm Width : 12.50 mm Length : 15.30 mm		
Operating lever			
HPQD6 (1W,2W,3W,4W)	Height : 14.85 mm Width : 13.00 mm Length : 31.70 mm		