



PS8M-8W

Terminal Type - PS8M - 8W , Plug & socket type terminal block , nominal voltage: 800 V , nominal current: 32 A, connection method: Screw clamp connection , number of connections: 16 , Rated cross section: 6 mm², cross section: 0.5 mm² - 6 mm², mounting type: TS35/7.5 , TS35/15

Product Accessories

| DIN Rail Perforated | | |
|------------------------|--|---|
| CHKDS | Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm |  |
| CHKS | Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm |  |
| DIN Rail, Unperforated | | |
| CHKD | Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm |  |
| CHK | Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm |  |
| End Cap | | |
| CHKENDCAP | Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm |  |
| End Clamp | | |
| SCUP | Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm |  |
| SCEC35 | Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm |  |
| SCUDD | Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm |  |
| SCUSL | Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm |  |

| End Clamp | | |
|-----------|---|---|
| SCKN | Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm |  |
| SCUN | Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm |  |

| Marker For Terminal Blocks | | |
|----------------------------|-----------------|---|
| LABEL KN6.5 | Width : 6.70 mm |  |

| Marker carriers | | |
|-----------------|--|---|
| SCUDDMLH | Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm |  |
| SCUNMLH | Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm |  |
| SCKNMLH | Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm |  |