



SPT240XL

Terminal Type - SPT240XL , High current connectors with secured hinged cover , nominal voltage: 1000 V AC/1500 V DC, nominal current: 415 A, connection method: Bolt connection , Bolt with clinched conical , number of connections: 2, cross section: 25 mm² - 240 mm² , 8 AWG-600 KCMIL, mounting type: TS 35/7.5 and TS 35/15

Product Accessories

DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	

Fixed Bridge		
CCLASPT240-2W	Width : 35.00 mm Thickness : 3.20 mm Pitch : 55.00 mm Length : 95.00 mm	
CCLASPT240-3W	Width : 35.00 mm Thickness : 3.20 mm Pitch : 55.00 mm Length : 150.00 mm	
Marker For Terminal Blocks		
LABEL KN12	Height : 2.43 mm Width : 12.00 mm Length : 8.50 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	
GMH10	Height : 51.00 mm Width : 10.00 mm Length : 42.25 mm	
GMH20	Height : 51.00 mm Width : 20.00 mm Length : 42.25 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	