









## SPT35XL

Terminal Type - SPT35XL , High current connectors with secured hinged cover , nominal voltage: 1000 V AC/1500 V DC, nominal current: 125 A, connection method: Bolt connection , Bolt with clinched conical , number of connections: 2, cross section: 10 mm<sup>2</sup> - 35 mm<sup>2</sup> , AWG: 14 - 2, mounting type: TS 35/7.5 and TS 35/15

### Product Accessories

| DIN Rail Perforated    |                                                                                      |                                                                                       |
|------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| CHKDS                  | Height : 15.00 mm<br>Width : 35.00 mm<br>Thickness : 1.50 mm<br>Length : 2,000.00 mm |    |
| CHKS                   | Height : 7.50 mm<br>Width : 35.00 mm<br>Thickness : 1.00 mm                          |    |
| DIN Rail, Unperforated |                                                                                      |                                                                                       |
| CHKD                   | Height : 15.00 mm<br>Width : 35.00 mm<br>Thickness : 1.50 mm                         |   |
| CHK                    | Height : 7.50 mm<br>Width : 35.00 mm<br>Thickness : 1.00 mm                          |  |
| End Cap                |                                                                                      |                                                                                       |
| CHKENDCAP              | Height : 14.00 mm<br>Width : 9.00 mm<br>Length : 41.50 mm                            |  |
| End Clamp              |                                                                                      |                                                                                       |
| SCUP                   | Height : 34.00 mm<br>Width : 9.00 mm<br>Length : 44.75 mm                            |  |
| SCUDD                  | Height : 50.00 mm<br>Width : 10.00 mm<br>Length : 55.60 mm                           |  |
| SCUSL                  | Height : 41.10 mm<br>Width : 8.00 mm<br>Length : 47.50 mm                            |  |

| Fixed Bridge |                                                                                  |                                                                                     |
|--------------|----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| CCLASPT35-2W | Width : 15.00 mm<br>Thickness : 3.00 mm<br>Pitch : 27.00 mm<br>Length : 42.00 mm |  |
| CCLASPT35-3W | Width : 15.00 mm<br>Thickness : 3.00 mm<br>Pitch : 27.00 mm<br>Length : 69.00 mm |  |

| Marker carriers |                                                            |                                                                                       |
|-----------------|------------------------------------------------------------|---------------------------------------------------------------------------------------|
| SCUDDMLH        | Height : 71.50 mm<br>Width : 11.00 mm<br>Length : 55.60 mm |    |
| GMH10           | Height : 51.00 mm<br>Width : 10.00 mm<br>Length : 42.25 mm |    |
| GMH20           | Height : 51.00 mm<br>Width : 20.00 mm<br>Length : 42.25 mm |   |
| SCKNMLH         | Height : 42.00 mm<br>Width : 16.00 mm<br>Length : 44.70 mm |  |