

## SQ16-1X2

Terminal Type - SQ16-1X2 , Multi conductor feed through terminal block, nominal voltage: 1000 V, nominal current: 76 A, connection method: Spring Cage Connection, number of connections: 2, cross section: 0.2 mm<sup>2</sup> - 25 mm<sup>2</sup>, AWG: 24-4 , mounting type: TS 35/7.5, TS 35/15

### Product Accessories

Cover Profile		
PCP250	Width : 49.00 mm Thickness : 1.50 mm Length : 166.00 mm	
DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	

<b>End Clamp</b>		
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
<b>End Cover</b>		
CSP16-1X2	Height : 37.20 mm Thickness : 2.00 mm Length : 110.30 mm	
<b>Marker For Terminal Blocks</b>		
LABEL KN12	Height : 2.43 mm Width : 12.00 mm Length : 8.50 mm	
<b>Partition Plate</b>		
BPA 185/240	Height : 82.50 mm Width : 3.00 mm Length : 180.00 mm	
<b>Plug-in Bridge/Jumper</b>		
SLPU12-2W	Height : 37.00 mm Width : 5.00 mm Pitch : 12.00 mm Length : 23.00 mm	

Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	
DCKNGML	Height : 31.10 mm Width : 8.45 mm Thickness : 29.35 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	

