










SQ4-2X2

Terminal Type – SQ4-2X2 , Multi Conductor feed through terminal block , connection method: Spring Cage Connection , Nominal Voltage : 1000 V , Nominal Current : 32 A , Rated cross section: 4.0 mm², Number of connections: 4, cross section: 0.08 mm² – 6 mm² , AWG : 24-10 , mounting type: TS 35/7.5, TS 35/15

Product Accessories

Cover Profile		
PCPDBF-5	Height : 14.10 mm Thickness : 1.50 mm Length : 113.00 mm	
DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	

End Clamp		
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
CSP4-2X2	Height : 22.70 mm Width : 2.00 mm Length : 90.20 mm	
Marker For Terminal Blocks		
LABEL KN5.5	Width : 6.00 mm	
Partition Plate		
DBF-5	Height : 42.45 mm Width : 3.00 mm Length : 112.00 mm	
Plug-in Bridge/Jumper		
SLPU6-2W	Height : 26.00 mm Width : 10.15 mm Pitch : 6.00 mm	

Plug-in Bridge/Jumper		
SLPU6-10W	Height : 26.00 mm Width : 58.15 mm Pitch : 6.00 mm	
SLPU6-3W	Height : 26.00 mm Width : 16.15 mm Pitch : 6.00 mm	
SLPU6-4W	Height : 26.00 mm Width : 22.15 mm Thickness : 2.50 mm Pitch : 6.25 mm	
SLPU6-5W	Height : 26.00 mm Width : 28.15 mm Pitch : 6.00 mm	
SLPU6-6W	Height : 26.00 mm Width : 34.15 mm Pitch : 6.00 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	