



## TQF6

Terminal Type - TQF6, Fuse terminal block, nominal voltage: 1000 V, nominal current: 10 A , Rated cross-section – 6 mm<sup>2</sup>, suitable size of cartridge fuse: 6.35X32 mm, connection method: Screw connection, number of connections: 2, cross-section: 0.2 mm<sup>2</sup> - 10 mm<sup>2</sup>, mounting type: TS 35/7.5, TS 35/15

### Product Accessories

| DIN Rail Perforated    |  |   |
|------------------------|--|---|
| CHKDS                  | Height : 15.00 mm<br>Width : 35.00 mm<br>Thickness : 1.50 mm<br>Length : 2,000.00 mm |    |
| CHKS                   | Height : 7.50 mm<br>Width : 35.00 mm<br>Thickness : 1.00 mm                          |    |
| DIN Rail, Unperforated |  |   |
| CHKD                   | Height : 15.00 mm<br>Width : 35.00 mm<br>Thickness : 1.50 mm                         |   |
| CHK                    | Height : 7.50 mm<br>Width : 35.00 mm<br>Thickness : 1.00 mm                          |  |
| End Cap                |  |   |
| CHKENDCAP              | Height : 14.00 mm<br>Width : 9.00 mm<br>Length : 41.50 mm                            |  |
| End Clamp              |  |   |
| SCUP                   | Height : 34.00 mm<br>Width : 9.00 mm<br>Length : 44.75 mm                            |  |
| SCEC35                 | Height : 31.50 mm<br>Width : 8.00 mm<br>Length : 45.80 mm                            |  |
| SCUSL                  | Height : 41.10 mm<br>Width : 8.00 mm<br>Length : 47.50 mm                            |  |
| SCUDD                  | Height : 50.00 mm<br>Width : 10.00 mm<br>Length : 55.60 mm                           |  |

| <b>End Clamp</b>                  |  |   |
|-----------------------------------|--|---|
| DCKN                              | Height : 33.00 mm<br>Width : 6.00 mm<br>Length : 43.50 mm                    |    |
| DCKN10                            | Height : 35.00 mm<br>Width : 10.00 mm<br>Length : 43.50 mm                   |    |
| SCKN                              | Height : 34.50 mm<br>Width : 8.00 mm<br>Length : 44.90 mm                    |    |
| SCUN                              | Height : 35.50 mm<br>Width : 9.50 mm<br>Length : 50.60 mm                    |    |
| <b>Marker For Terminal Blocks</b> |  |   |
| LABEL KN8                         | Height : 2.43 mm<br>Width : 8.00 mm<br>Length : 8.50 mm                      |   |
| <b>Partition Plate</b>            |  |   |
| DBF-6                             | Height : 81.50 mm<br>Width : 3.00 mm<br>Length : 85.00 mm                    |  |
| <b>Plug-in Bridge/Jumper</b>      |  |   |
| MLPU8-10W                         | Height : 26.00 mm<br>Width : 3.00 mm<br>Pitch : 8.00 mm<br>Length : 79.20 mm |  |
| MLPU8-2W                          | Height : 26.00 mm<br>Width : 3.00 mm<br>Pitch : 8.00 mm<br>Length : 15.20 mm |  |
| MLPU8-3W                          | Height : 26.00 mm<br>Width : 3.00 mm<br>Pitch : 8.00 mm<br>Length : 23.20 mm |  |
| MLPU8-4W                          | Height : 26.00 mm<br>Width : 3.00 mm<br>Pitch : 8.00 mm<br>Length : 31.20 mm |  |

| Plug-in Bridge/Jumper |  |   |
|-----------------------|--|---|
| MLPU8-5W              | Height : 26.00 mm<br>Width : 3.00 mm<br>Pitch : 8.00 mm<br>Length : 39.20 mm |  |
| MLPU8-6W              | Height : 26.00 mm<br>Width : 3.00 mm<br>Pitch : 8.00 mm<br>Length : 47.20 mm |  |

| Marker carriers |  |   |
|-----------------|--|---|
| SCUDDMLH        | Height : 71.50 mm<br>Width : 11.00 mm<br>Length : 55.60 mm |    |
| SCUNMLH         | Height : 53.50 mm<br>Width : 11.00 mm<br>Length : 50.60 mm |    |
| DCKNMLH         | Height : 45.00 mm<br>Width : 10.00 mm<br>Length : 43.50 mm |   |
| SCKNMLH         | Height : 42.00 mm<br>Width : 16.00 mm<br>Length : 44.70 mm |  |