



TQK6

Terminal Type - TQK6, Knife Disconnect Terminal block, nominal voltage: 1000 V, nominal current: 22 A, Rated cross-section - 6.0 mm², connection method: Screw connection, number of connections: 2, Rated cross-section: 0.2 mm² - 10 mm², mounting type: TS 35/7.5, TS 35/15

Product Accessories

| Cover Profile | | |
|------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| PCPDBF-3 | Height : 14.10 mm Thickness : 1.50 mm Length : 79.00 mm |  |
| DIN Rail Perforated | | |
| CHKDS | Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm |  |
| CHKS | Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm |  |
| DIN Rail, Unperforated | | |
| CHKD | Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm |  |
| CHK | Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm |  |
| End Cap | | |
| CHKENDCAP | Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm |  |
| End Clamp | | |
| SCUP | Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm |  |
| SCEC35 | Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm |  |

| End Clamp | | |
|-----------------------------------|------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| SCUSL | Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm |  |
| SCUDD | Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm |  |
| DCKN | Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm |  |
| DCKN10 | Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm |  |
| SCKN | Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm |  |
| SCUN | Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm |  |
| Marker For Terminal Blocks | | |
| LABEL KN8 | Height : 2.43 mm Width : 8.00 mm Length : 8.50 mm |  |
| Partition Plate | | |
| DBF-3 | Height : 50.00 mm Width : 3.00 mm Length : 78.00 mm |  |
| Plug-in Bridge/Jumper | | |
| MLPU8-10W | Height : 26.00 mm Width : 3.00 mm Pitch : 8.00 mm Length : 79.20 mm |  |
| MLPU8-2W | Height : 26.00 mm Width : 3.00 mm Pitch : 8.00 mm Length : 15.20 mm |  |

| Plug-in Bridge/Jumper | | |
|-----------------------|------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| MLPU8-3W | Height : 26.00 mm Width : 3.00 mm Pitch : 8.00 mm Length : 23.20 mm |  |
| MLPU8-4W | Height : 26.00 mm Width : 3.00 mm Pitch : 8.00 mm Length : 31.20 mm |  |
| MLPU8-5W | Height : 26.00 mm Width : 3.00 mm Pitch : 8.00 mm Length : 39.20 mm |  |
| MLPU8-6W | Height : 26.00 mm Width : 3.00 mm Pitch : 8.00 mm Length : 47.20 mm |  |

| Marker carriers | | |
|-----------------|------------------------------------------------------------|---------------------------------------------------------------------------------------|
| SCUDDMLH | Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm |  |
| SCUNMLH | Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm |  |
| DCKNMLH | Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm |  |
| SCKNMLH | Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm |  |