












CLTDM4

Terminal Type - CLTDM4 , Test Disconnect Terminal Block , nominal voltage: 1100 V, nominal current: 45 A, connection method: Bolt connection, number of connections: 2, Rated cross section: 6 mm², cross section: 2.5 mm² - 6 mm² , mounting type: TS32

Product Accessories

Cover Profile		
PCD 39	Height : 26.00 mm Thickness : 1.50 mm Length : 70.00 mm	
PCD26	Height : 26.00 mm Thickness : 1.50 mm Length : 70.00 mm	
PCD3	Height : 26.20 mm Width : 73.00 mm Thickness : 1.50 mm	
DIN Rail Perforated		
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
End Clamp		
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCSN	Height : 31.00 mm Width : 8.40 mm Length : 27.00 mm	
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	

End Clamp		
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
EPLD4	Height : 36.90 mm Width : 2.50 mm Length : 69.00 mm	
Insertion Bridge		
ADSL-10W	Width : 124.50 mm Pitch : 13.00 mm Length : 24.00 mm	
ADSL-2W	Width : 20.50 mm Pitch : 13.00 mm Length : 24.00 mm	
ADSL-3W	Width : 33.50 mm Pitch : 13.00 mm Length : 24.00 mm	
ADSL-4W	Width : 46.50 mm Pitch : 13.00 mm Length : 24.00 mm	
ADSL-7W	Width : 85.50 mm Pitch : 13.00 mm Length : 24.00 mm	
Marker For Terminal Blocks		
LABEL KN5.5	Width : 6.00 mm	

Marker carriers		
GMC	Height : 48.00 mm Width : 39.00 mm Thickness : 1.00 mm Length : 38.00 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	