


CBTM5

Terminal Type - CBTM5, Feed Through Terminal Block, nominal voltage: 1100 V, nominal current: 76 A , Rated cross-section - 16 mm², connection method: Bolt Connection - Nut driver operated , number of connections: 2, cross section: 2.5 mm² - 16 mm², mounting type :TS32



Approvals



General Information

| | |
|------------------------------|---|
| Product Name | CBTM5 |
| Connection Method | Bolt Connection |
| Rating | 1100 V / 76 A / 16 mm ² / 2 Nm |
| HSN Number | 85389000 |
| Standard Packing Qty (in No) | 50 |
| Country Of Origin | India |
| Screw thread | M5 |

Dimensions & Weight

| | | |
|-----------------------------|---------|-----------|
| Width | 15 mm | 0.59 inch |
| Length | 46 mm | 1.81 inch |
| Height | 42 mm | 1.65 inch |
| Weight of std. Packing Unit | 1.42 Kg | |

Material Data

| | |
|---------------------|--------------------------------|
| Insulating Material | Melamine |
| Standard Colour | Khakhi |
| Colour Variants | Red, Yellow, Blue, Black, Gray |

Rated Conductor Size



| | |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 2.5 mm ² |
| Conductor cross section flexible max | 16 mm ² |
| Conductor cross section solid min | 2.5 mm ² |
| Conductor cross section solid max | 16 mm ² |


Rated Conductor Size

| | |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 2.5 mm ² |
| Conductor cross section flexible max | 16 mm ² |

| | |
|-----------------------------------|---------------------|
| Conductor cross section solid min | 2.5 mm ² |
| Conductor cross section solid max | 16 mm ² |

Product Accessories

| Cover Profile | | |
|---------------|---|---|
| PCC3NV | Width : 300.00 mm Thickness : 1.50 mm Length : 48.50 mm |  |
| PCCM30NV | Width : 30.00 mm Thickness : 1.00 mm Length : 45.50 mm |  |
| PCCM45K | Height : 13.15 mm Width : 45.00 mm Thickness : 1.30 mm |  |

| DIN Rail Perforated | | |
|---------------------|--|--|
| CHS | Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm |  |

| End Clamp | | |
|-----------|--|---|
| SCS | Height : 26.90 mm Length : 21.00 mm |  |
| SCSN | Height : 31.00 mm Width : 8.40 mm Length : 27.00 mm |  |
| SCUP | Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm |  |
| SCUSL | Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm |  |
| SCUDD | Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm |  |
| SCUN | Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm |  |

| End Cover | | |
|-----------------------------------|---|---|
| EPS4NV | Height : 28.50 mm Width : 2.50 mm Length : 46.00 mm |  |
| Insertion Bridge | | |
| KSL5-10W | Width : 142.50 mm Pitch : 15.00 mm Length : 26.50 mm |  |
| KSL5-2W | Width : 37.50 mm Pitch : 15.00 mm Length : 26.00 mm |  |
| KSL5-3W | Width : 22.50 mm Pitch : 15.00 mm Length : 26.00 mm |  |
| KSL5-4W | Width : 52.50 mm Pitch : 15.00 mm Length : 26.00 mm |  |
| KSL5-5W | Width : 67.50 mm Pitch : 15.00 mm Length : 26.00 mm |  |
| Marker For Terminal Blocks | | |
| LABEL KN6.5 | Width : 6.70 mm |  |
| Partition Plate | | |
| KBZF | Height : 65.00 mm Width : 1.50 mm Length : 65.00 mm |  |
| Marker carriers | | |
| GMC | Height : 48.00 mm Width : 39.00 mm Thickness : 1.00 mm Length : 38.00 mm |  |
| SCUDDMLH | Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm |  |

Marker carriers

| | | |
|---------|--|---|
| SCUNMLH | Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm |  |
|---------|--|---|

