


CLTDM4

Terminal Type - CLTDM4 , Test Disconnect Terminal Block , nominal voltage: 1100 V, nominal current: 45 A, connection method: Bolt connection, number of connections: 2, Rated cross section: 6 mm², cross section: 2.5 mm² - 6 mm² , mounting type: TS32



Approvals



General Information

| | |
|------------------------------|--|
| Product Name | CLTDM4 |
| Connection Method | Bolt Connection |
| Rating | 1100 V / 45 A / 6 mm ² / 1.2 Nm |
| HSN Number | 85389000 |
| Standard Packing Qty (in No) | 50 |
| Country Of Origin | INDIA |
| Screw thread | M4 |

Dimensions & Weight

| | | |
|-----------------------------|---------|-----------|
| Width | 13 mm | 0.51 inch |
| Length | 69 mm | 2.72 inch |
| Height | 50 mm | 1.97 inch |
| Weight of std. Packing Unit | 2.21 Kg | |

Material Data

| | |
|---------------------|---------------------------------|
| Insulating Material | Melamine |
| Standard Colour | Khakhi |
| Colour Variants | Red, Yellow, Blue, Black, Green |

Rated Conductor Size

| | |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 2.5 mm ² |
| Conductor cross section flexible max | 6 mm ² |
| Conductor cross section solid min | 2.5 mm ² |
| Conductor cross section solid max | 6 mm ² |

Rated Conductor Size

| | |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 2.5 mm ² |
| Conductor cross section flexible max | 6 mm ² |
| Conductor cross section solid min | 2.5 mm ² |

| | |
|-----------------------------------|-------------------|
| Conductor cross section solid max | 6 mm ² |
|-----------------------------------|-------------------|

Product Accessories

| Cover Profile | | |
|----------------------------|---|---|
| PCD 39 | Height : 26.00 mm Thickness : 1.50 mm Length : 70.00 mm |  |
| PCD26 | Height : 26.00 mm Thickness : 1.50 mm Length : 70.00 mm |  |
| PCD3 | Height : 26.20 mm Width : 73.00 mm Thickness : 1.50 mm |  |
| DIN Rail Perforated | | |
| CHS | Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm |  |
| End Clamp | | |
| SCEC35 | Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm |  |
| SCSN | Height : 31.00 mm Width : 8.40 mm Length : 27.00 mm |  |
| SCUP | Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm |  |
| SCUSL | Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm |  |
| SCUDD | Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm |  |
| DCKN | Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm |  |

| End Clamp | | |
|-----------------------------------|---|---|
| DCKN10 | Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm |  |
| SCUN | Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm |  |
| End Cover | | |
| EPLD4 | Height : 36.90 mm Width : 2.50 mm Length : 69.00 mm |  |
| Insertion Bridge | | |
| ADSL-10W | Width : 124.50 mm Pitch : 13.00 mm Length : 24.00 mm |  |
| ADSL-2W | Width : 20.50 mm Pitch : 13.00 mm Length : 24.00 mm |  |
| ADSL-3W | Width : 33.50 mm Pitch : 13.00 mm Length : 24.00 mm |  |
| ADSL-4W | Width : 46.50 mm Pitch : 13.00 mm Length : 24.00 mm |  |
| ADSL-7W | Width : 85.50 mm Pitch : 13.00 mm Length : 24.00 mm |  |
| Marker For Terminal Blocks | | |
| LABEL KN5.5 | Height : 2.42 mm Width : 6.00 mm Length : 7.50 mm |  |
| Marker carriers | | |
| GMC | Height : 48.00 mm Width : 39.00 mm Thickness : 1.00 mm Length : 38.00 mm |  |

Marker carriers

| | | |
|---------|--|---|
| SCUNMLH | Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm |  |
|---------|--|---|

