


CST10

Terminal Type - CST10 , Feed Through Terminal block, nominal voltage: 800 V, nominal current: 57 A , Rated cross-section - 10 mm², connection method: Screw connection, number of connections: 2, cross section: 0.5 mm² - 16 mm², mounting type: TS32



Approvals



General Information

Product Name	CST10
Connection Method	Screw Connection
Rating	800 V / 57 A / 10 mm ² / 1.2 Nm
HSN Number	85389000
Standard Packing Qty (in No)	100
Country Of Origin	India
Screw thread	M4

Dimensions & Weight

Width	10 mm	0.39 inch
Length	40 mm	1.57 inch
Height	49 mm	1.93 inch
Weight of std. Packing Unit	2.55 Kg	

Material Data

Insulating Material	Melamine
Standard Colour	Khakhi
Colour Variants	Red, Yellow, Blue, Black, Green

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	10 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	16 mm ²

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	10 mm ²
Conductor cross section solid min	0.5 mm ²

Conductor cross section solid max	16 mm ²
-----------------------------------	--------------------

Product Accessories

Cover Profile		
PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
Cover Profile Carrier		
UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
DIN Rail Perforated		
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
End Clamp		
SCS	Height : 26.90 mm Length : 21.00 mm	
SCSN	Height : 31.00 mm Width : 8.40 mm Length : 27.00 mm	
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	

End Cover		
EPX	Height : 48.60 mm Width : 2.00 mm Length : 39.60 mm	
Fixed Bridge		
CCLA10-2W	Height : 20.00 mm Pitch : 10.00 mm Length : 17.30 mm	
CCLA10-10W	Height : 20.00 mm Pitch : 10.00 mm Length : 97.50 mm	
CCLA10-3W	Height : 20.00 mm Pitch : 10.00 mm Length : 27.30 mm	
CCLA10-4W	Height : 20.00 mm Pitch : 10.00 mm Length : 37.30 mm	
CCLA10-5W	Height : 20.00 mm Pitch : 10.00 mm	
CCLA10-6W	Height : 20.00 mm Pitch : 10.00 mm Length : 57.40 mm	
CCLA10-7W	Height : 20.00 mm Pitch : 10.00 mm Length : 67.40 mm	
CCLA10-8W	Height : 20.00 mm Pitch : 10.00 mm Length : 77.40 mm	
Insertion Bridge		
SLC10N-2W	Width : 17.50 mm Pitch : 10.00 mm Length : 26.50 mm	
SLC10N-10W	Width : 97.50 mm Pitch : 10.00 mm Length : 26.50 mm	

Insertion Bridge		
SLC10N-4W	Width : 37.50 mm Pitch : 10.00 mm Length : 26.50 mm	
SLC10N-6W	Width : 57.50 mm Pitch : 10.00 mm Length : 26.50 mm	
Marker For Terminal Blocks		
LABEL KN10	Height : 2.89 mm Width : 10.00 mm Length : 8.50 mm	
Partition Plate		
BPX	Height : 60.00 mm Width : 3.00 mm Length : 55.00 mm	
KBXF	Height : 53.40 mm Width : 1.50 mm Length : 54.00 mm	
Switching Jumper		
LSR10-16	Width : 6.00 mm	
RSL10	Thickness : 1.60 mm Pitch : 10.00 mm Length : 17.00 mm	
Warning Label		
WL10	Width : 28.00 mm Thickness : 1.50 mm Length : 39.00 mm	
Marker carriers		
GMC	Height : 48.00 mm Width : 39.00 mm Thickness : 1.00 mm Length : 38.00 mm	
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	

Marker carriers		
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	

