


## CST16

Terminal Type - CST16, Feed Through Terminal block, nominal voltage: 800 V, nominal current: 76 A , Rated cross-section - 16 mm<sup>2</sup>, connection method: Screw connection, number of connections: 2, cross-section: 6 mm<sup>2</sup> - 25 mm<sup>2</sup>, mounting type: TS32



### Approvals



### General Information

Product Name	CST16
Connection Method	Screw Connection
Rating	800 V / 76 A / 16 mm <sup>2</sup> / 1.2 Nm
HSN Number	85389000
Standard Packing Qty (in No)	50
Country Of Origin	India
Screw thread	M4

### Dimensions & Weight

Width	12 mm	0.47 inch
Length	45 mm	1.77 inch
Height	55 mm	2.17 inch
Weight of std. Packing Unit	2.54 Kg	

### Material Data

Insulating Material	Melamine
Standard Colour	Khakhi
Colour Variants	Red, Yellow, Blue, Black, Green

### Rated Conductor Size

Conductor cross section flexible min	6 mm <sup>2</sup>
Conductor cross section flexible max	16 mm <sup>2</sup>
Conductor cross section solid min	6 mm <sup>2</sup>
Conductor cross section solid max	25 mm <sup>2</sup>

### Rated Conductor Size

Conductor cross section flexible min	6 mm <sup>2</sup>
Conductor cross section flexible max	16 mm <sup>2</sup>
Conductor cross section solid min	6 mm <sup>2</sup>

Conductor cross section solid max	25 mm <sup>2</sup>
-----------------------------------	--------------------

**Product Accessories**

<b>Cover Profile</b>		
PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
<b>Cover Profile Carrier</b>		
UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
<b>DIN Rail Perforated</b>		
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
<b>End Clamp</b>		
SCS	Height : 26.90 mm Length : 21.00 mm	
SCSN	Height : 31.00 mm Width : 8.40 mm Length : 27.00 mm	
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	

<b>End Cover</b>		
EPY	Height : 41.90 mm Width : 2.50 mm Length : 44.90 mm	
<b>Fixed Bridge</b>		
CCLA16-2W	Height : 24.20 mm Width : 6.00 mm Pitch : 12.00 mm Length : 21.00 mm	
CCLA16-10W	Height : 24.20 mm Width : 6.00 mm Pitch : 12.00 mm Length : 117.00 mm	
CCLA16-3W	Height : 24.20 mm Width : 6.00 mm Pitch : 12.00 mm Length : 33.00 mm	
CCLA16-4W	Height : 24.20 mm Width : 6.00 mm Pitch : 12.00 mm Length : 45.00 mm	
CCLA16-5W	Height : 24.20 mm Width : 6.00 mm Pitch : 12.00 mm Length : 57.00 mm	
CCLA16-6W	Height : 24.20 mm Width : 6.00 mm Pitch : 12.00 mm Length : 69.00 mm	
<b>Marker For Terminal Blocks</b>		
LABEL KN10	Height : 2.89 mm Width : 10.00 mm Length : 8.50 mm	
<b>Partition Plate</b>		
BPY	Height : 66.00 mm Width : 3.00 mm Length : 65.00 mm	
KBZF	Height : 65.00 mm Width : 1.50 mm Length : 65.00 mm	

Switching Jumper		
LSR10-16	Width : 6.00 mm	
RSL16	Thickness : 1.60 mm Pitch : 12.00 mm Length : 21.00 mm	
Warning Label		
WL16	Width : 30.00 mm Thickness : 1.50 mm Length : 50.00 mm	
Marker carriers		
GMC	Height : 48.00 mm Width : 39.00 mm Thickness : 1.00 mm Length : 38.00 mm	
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	