


CST2.5

Terminal Type - CST2.5, Feed Through Terminal block, nominal voltage: 800 V, nominal current: 32 A, Rated cross-section - 4.0 mm², connection method: Screw connection, number of connections: 2, cross-section: 0.5 mm² - 6 mm², mounting type: TS32



Approvals



General Information

Product Name	CST2.5
Connection Method	Screw Connection
Rating	800 V / 32 A / 4 mm ² / 0.5 Nm
HSN Number	85389000
Standard Packing Qty (in No)	100
Country Of Origin	India
Screw thread	M3

Dimensions & Weight

Width	6.7 mm	0.26 inch
Length	40 mm	1.57 inch
Height	49 mm	1.93 inch
Weight of std. Packing Unit	1.44 Kg	

Material Data

Insulating Material	Melamine
Standard Colour	Khakhi
Colour Variants	Red, Yellow, Blue, Black, Green

Rated Conductor Size








Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	4 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	6 mm ²



Rated Conductor Size


Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	4 mm ²
Conductor cross section solid min	0.5 mm ²

Conductor cross section solid max	6 mm ²
-----------------------------------	-------------------

Product Accessories

Cover Profile		
PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
Cover Profile Carrier		
UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
DIN Rail Perforated		
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
End Clamp		
SCS	Height : 26.90 mm Length : 21.00 mm	
SCSN	Height : 31.00 mm Width : 8.40 mm Length : 27.00 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
EPX	Height : 48.60 mm Width : 2.00 mm Length : 39.60 mm	

Fixed Bridge		
CCLA2.5-10W	Height : 24.12 mm Width : 5.00 mm Pitch : 6.75 mm Length : 66.00 mm	
CCLA2.5-3W	Height : 24.12 mm Width : 5.00 mm Pitch : 6.75 mm Length : 18.85 mm	
CCLA2.5-4W	Height : 24.12 mm Width : 5.00 mm Pitch : 6.75 mm Length : 25.60 mm	
CCLA2.5-5W	Height : 24.12 mm Width : 5.00 mm Pitch : 6.75 mm Length : 32.35 mm	
CCLA2.5-6W	Height : 24.12 mm Width : 5.00 mm Pitch : 6.75 mm Length : 39.00 mm	
CCLA2.5-8W	Height : 24.12 mm Width : 5.00 mm Pitch : 6.75 mm Length : 52.60 mm	
CCLA2.5-2W	Height : 24.12 mm Width : 5.00 mm Pitch : 6.75 mm Length : 12.10 mm	
Insertion Bridge		
SLC2.5-2W	Height : 26.00 mm Width : 3.00 mm Pitch : 6.70 mm Length : 12.50 mm	
SLC2.5-10W	Height : 26.00 mm Width : 3.00 mm Pitch : 6.70 mm Length : 66.10 mm	
SLC2.5-4W	Height : 26.00 mm Width : 3.00 mm Pitch : 6.70 mm Length : 25.90 mm	
SLC2.5-5W	Height : 26.00 mm Width : 3.00 mm Pitch : 6.70 mm Length : 32.60 mm	

Insertion Bridge		
SLC2.5-3W	Height : 26.00 mm Width : 3.00 mm Pitch : 6.70 mm Length : 19.20 mm	
Marker For Terminal Blocks		
LABEL KN6.5	Width : 6.70 mm	
Partition Plate		
BPX	Height : 60.00 mm Width : 3.00 mm Length : 55.00 mm	
KBXF	Height : 53.40 mm Width : 1.50 mm Length : 54.00 mm	
Switching Jumper		
LSR2.5-6	Height : 23.00 mm Width : 5.00 mm	
RSL2.5	Thickness : 1.20 mm Pitch : 6.60 mm Length : 12.60 mm	
Warning Label		
WL4	Height : 25.20 mm Thickness : 1.10 mm Length : 28.80 mm	
Marker carriers		
GMC	Height : 48.00 mm Width : 39.00 mm Thickness : 1.00 mm Length : 38.00 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	