


CST6

Terminal Type - CST6, Feed Through Terminal block, nominal voltage: 800 V, nominal current: 41 A, Rated cross-section - 6.0 mm², connection method: Screw connection, number of connections: 2, cross-section: 0.5 mm² - 10 mm², mounting type: TS32



Approvals



General Information

Product Name	CST6
Connection Method	Screw Connection
Rating	800 V / 41 A / 6 mm ² / 0.8 Nm
HSN Number	85389000
Standard Packing Qty (in No)	100
Country Of Origin	India
Screw thread	M3.5

Dimensions & Weight

Width	8 mm	0.31 inch
Length	40 mm	1.57 inch
Height	49 mm	1.93 inch
Weight of std. Packing Unit	1.73 Kg	

Material Data

Insulating Material	Melamine
Standard Colour	Khakhi
Colour Variants	Red, Yellow, Blue, Black, Green

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	10 mm ²

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	0.5 mm ²


Conductor cross section solid max	10 mm ²
-----------------------------------	--------------------

Product Accessories

Cover Profile		
PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
Cover Profile Carrier		
UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
DIN Rail Perforated		
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
End Clamp		
SCS	Height : 26.90 mm Length : 21.00 mm	
SCSN	Height : 31.00 mm Width : 8.40 mm Length : 27.00 mm	
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	

End Cover		
EPX	Height : 48.60 mm Width : 2.00 mm Length : 39.60 mm	
Fixed Bridge		
CCLA6-2W	Height : 24.20 mm Width : 5.50 mm Pitch : 8.00 mm Length : 13.50 mm	
CCLA6-10W	Height : 24.20 mm Width : 5.50 mm Pitch : 8.00 mm Length : 78.10 mm	
CCLA6-3W	Height : 24.20 mm Width : 5.50 mm Pitch : 8.00 mm Length : 21.60 mm	
CCLA6-4W	Height : 24.20 mm Width : 5.50 mm Pitch : 8.00 mm Length : 29.70 mm	
CCLA6-5W	Height : 24.20 mm Width : 5.50 mm Pitch : 8.00 mm Length : 37.70 mm	
CCLA6-6W	Height : 24.20 mm Width : 5.50 mm Pitch : 8.00 mm Length : 45.80 mm	
CCLA6-7W	Height : 24.20 mm Width : 5.50 mm Pitch : 8.00 mm Length : 53.90 mm	
Insertion Bridge		
SLC6-10W	Height : 26.00 mm Width : 3.00 mm Pitch : 8.00 mm Length : 78.60 mm	
SLC6-3W	Height : 26.00 mm Width : 3.00 mm Pitch : 8.00 mm Length : 22.60 mm	
SLC6-4W	Height : 26.00 mm Width : 3.00 mm Pitch : 8.00 mm Length : 30.60 mm	

Insertion Bridge		
SLC6-5W	Height : 26.00 mm Width : 3.00 mm Pitch : 8.00 mm Length : 38.60 mm	
SLC6-6W	Height : 26.00 mm Width : 3.00 mm Pitch : 8.00 mm Length : 46.60 mm	
SLC6-2W	Height : 26.00 mm Width : 3.00 mm Pitch : 8.00 mm Length : 14.60 mm	
Marker For Terminal Blocks		
LABEL KN8	Height : 2.43 mm Width : 8.00 mm Length : 8.50 mm	
Partition Plate		
BPX	Height : 60.00 mm Width : 3.00 mm Length : 55.00 mm	
KBXF	Height : 53.40 mm Width : 1.50 mm Length : 54.00 mm	
Switching Jumper		
LSR2.5-6	Height : 23.00 mm Width : 5.00 mm	
RSL6	Thickness : 1.20 mm Pitch : 8.00 mm Length : 13.80 mm	
Warning Label		
WL6	Height : 28.00 mm Thickness : 1.10 mm Length : 31.00 mm	
Marker carriers		
GMC	Height : 48.00 mm Width : 39.00 mm Thickness : 1.00 mm Length : 38.00 mm	

Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	