


DMCT2.5P4

Terminal Type -DMCT2.5P4, Multi-Conductor - Mini and Micro terminal block, nominal voltage: 800 V, nominal current: 24 A, Rated cross-section - 2.5 mm², connection method: Spring clamp connection, number of connections: 4, cross-section: 0.5 mm² - 2.5 mm², mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

Product Name	DMCT2.5P4
Connection Method	Spring Cage Connection
Rating	800 V / 24 A / 2.5 mm ²
HSN Number	85389000
Standard Packing Qty (in No)	100
Country Of Origin	India
Screw thread	-

Dimensions & Weight

Width	10 mm	0.39 inch
Length	42.2 mm	1.66 inch
Height	27.9 mm	1.1 inch
Weight of std. Packing Unit	0.55 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	2.5 mm ²


Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	2.5 mm ²

Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	2.5 mm ²

Product Accessories

End Cover

DMEP2.5P4	Height : 21.05 mm Thickness : 2.00 mm Length : 35.60 mm	
-----------	---	---

Insertion Bridge

MSL2.5	Width : 10.30 mm Pitch : 5.95 mm Length : 15.14 mm	
--------	--	---

Marker For Terminal Blocks

LABEL KN10	Width : 10.00 mm	
------------	------------------	---