


DPBB185N

Terminal Type - DPBB185N, High Current connectors, nominal voltage: 1000 V, nominal current: 353 A, Rated cross-section - 185 mm², connection method: Bolt connection, number of connections: 2, cross-section: 50 mm² - 185 mm², mounting type: TS 35/15, TS 32



Approvals



General Information

Product Name	DPBB185N
Connection Method	Bolt Connection
Rating	1000 V / 353 A / 185 mm ² / 14 Nm
HSN Number	85389000
Standard Packing Qty (in No)	4
Country Of Origin	India
Screw thread	M12

Dimensions & Weight

Width	53 mm	2.09 inch
Length	115 mm	4.53 inch
Height	53.3 mm	2.1 inch
Weight of std. Packing Unit	1.49 Kg	






Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khaki

Rated Conductor Size

Conductor cross section flexible min	50 mm ²
Conductor cross section flexible max	185 mm ²
Conductor cross section solid min	50 mm ²
Conductor cross section solid max	185 mm ²

Product Accessories

Cover Profile		
PCP240-2W	Width : 111.00 mm Thickness : 1.50 mm Length : 186.00 mm	
DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
Marker For Terminal Blocks		
LABEL KN10	Height : 2.89 mm Width : 10.00 mm Length : 8.50 mm	

Partition Plate		
BPA185/240	Height : 82.50 mm Width : 3.00 mm Length : 180.00 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	

