


DPBB70

Terminal Type - DPBB70, High current connectors, nominal voltage: 1000 V, nominal current: 192 A, Rated cross-section – 70 mm², connection method: Bolt connection, number of connections: 2, cross-section: 10 mm² - 70 mm², AWG: 6 - 2/0, mounting type: TS 35/7.5, TS 35/15, TS 32



Approvals



General Information

Product Name	DPBB70
Connection Method	Bolt Connection
Rating	1000 V / 192 A / 70 mm ² / 3 Nm
HSN Number	85389000
Standard Packing Qty (in No)	10
Country Of Origin	India
Screw thread	M6

Dimensions & Weight

Width	37.2 mm	1.46 inch
Length	90 mm	3.54 inch
Height	44 mm	1.73 inch
Weight of std. Packing Unit	1.05 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	10 mm ²
Conductor cross section flexible max	70 mm ²
Conductor cross section solid min	10 mm ²
Conductor cross section solid max	70 mm ²

Rated Conductor Size

Conductor cross section flexible min	10 mm ²
Conductor cross section flexible max	70 mm ²

Conductor cross section solid min	10 mm ²
Conductor cross section solid max	70 mm ²

Ratings - ATEX

ATEX Standard	EN 60079-7
ATEX Nominal Voltage U _n	1000 V
ATEX Nominal Current I _n	192 A
ATEX Cross Sec. Flexible Max.	70 mm ²

Ratings - CSA

CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage U _N	1000 V
B - CSA Nominal Current I _N	175 A
B - CSA Wire Min	6 AWG
B - CSA Wire Max	2/0 AWG

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U _N	1000 V
B - UL Nominal Current I _N	175 A
B - UL Wire Min	6 AWG
B - UL Wire Max	2/0 AWG

Product Accessories

Cover Profile





PCP120	Width : 41.00 mm Thickness : 1.50 mm Length : 126.00 mm	
--------	---	---

DIN Rail Perforated

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

DIN Rail, Unperforated

CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
------	--	---

DIN Rail, Unperforated		
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
Marker For Terminal Blocks		
LABEL KN10	Width : 10.00 mm	
Partition Plate		
BPN70	Height : 67.50 mm Width : 3.00 mm Length : 125.00 mm	
Marker carriers		
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	