



## DPSC5.08PMV-16W

Terminal Type - DPSC5.08PMV-16W , Plug & socket type terminal block , nominal voltage: 250 V, nominal current: 16 A, connection method: Spring cage connection, number of connections: 32 , cross-section: 0.2 mm<sup>2</sup> - 2.5 mm<sup>2</sup>, Rated Cross section - 2.5 mm<sup>2</sup> , AWG : 24-12 , mounting type: Panel mounting / Surface mounting



### Approvals



### General Information

Product Name	DPSC5.08PMV-16W
Connection Method	Spring Cage Connection
Rating	250 V / 16 A / 2.5 mm <sup>2</sup> / Nm
HSN Number	85389000
Standard Packing Qty (in No)	50
Country Of Origin	India
Screw thread	NAV

### Dimensions & Weight

Width	97.1 mm	3.82 inch
Length	45.25 mm	1.78 inch
Height	14.5 mm	0.57 inch
Weight of std. Packing Unit	2.5 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	-

### Rated Conductor Size

Conductor cross section flexible min	0.2 mm <sup>2</sup>
Conductor cross section flexible max	2.5 mm <sup>2</sup>
Conductor cross section solid min	0.2 mm <sup>2</sup>
Conductor cross section solid max	2.5 mm <sup>2</sup>

### Rated Conductor Size

Conductor cross section flexible min	0.2 mm <sup>2</sup>
Conductor cross section flexible max	2.5 mm <sup>2</sup>

Conductor cross section solid min	0.2 mm <sup>2</sup>
Conductor cross section solid max	2.5 mm <sup>2</sup>

### Ratings - UL


UL Standard	UL 1059
B - UL Nominal Voltage U <sub>N</sub>	300 V
B - UL Nominal Current I <sub>N</sub>	16 A
B - UL Wire Min	24 AWG
B - UL Wire Max	12 AWG

### Product Accessories

#### Marker For Terminal Blocks

LABEL KN5.08	Pitch : 5.08 mm	
--------------	-----------------	---

#### Tool

DPSCCOT	Height : 6.90 mm Width : 5.00 mm Length : 20.30 mm	
---------	--	--