



DPSC5.08WF-6W

Terminal Type - DPSC5.08WF - 6W , Plug & socket type terminal block , nominal voltage: 250 V, nominal current: 16 A, connection method: Spring cage connection , number of connections: 12, cross section: 0.2 mm² - 2.5 mm², Rated cross-section - 2.5 mm², AWG : 24-12 , mounting type: TS35/7.5 , TS35/15



Approvals



General Information

Product Name	DPSC5.08WF-6W
Connection Method	Spring Cage Connection
Rating	250 V / 16 A / 2.5 mm ² / Nm
HSN Number	85389000
Standard Packing Qty (in No)	25
Country Of Origin	India
Screw thread	NAV

Dimensions & Weight

Width	46.37 mm	1.83 inch
Length	58.51 mm	2.3 inch
Height	26.15 mm	1.03 inch
Weight of std. Packing Unit	0.7 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	0.2 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.2 mm ²
Conductor cross section solid max	2.5 mm ²

Rated Conductor Size

Conductor cross section flexible min	0.2 mm ²
Conductor cross section flexible max	2.5 mm ²


Conductor cross section solid min	0.2 mm ²
Conductor cross section solid max	2.5 mm ²

Ratings - UL


UL Standard	UL 1059
B - UL Nominal Voltage U _N	300 V
B - UL Nominal Current I _N	16 A
B - UL Wire Min	24 AWG
B - UL Wire Max	12 AWG

Product Accessories


DIN Rail Perforated

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

DIN Rail, Unperforated

CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	


End Cap

CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
-----------	---	---

Marker For Terminal Blocks

LABEL KN5.08	Pitch : 5.08 mm	
--------------	-----------------	---

Tool

DPSCCOT	Height : 6.90 mm Width : 5.00 mm Length : 20.30 mm	
---------	--	---