



DPSC5.08WW-4W

Terminal Type - DPSC5.08WW - 4W , Plug & socket type terminal block , nominal voltage: 250 V, nominal current: 16 A, Rated cross-section - 2.5 mm², connection method: Spring cage connection, number of connections: 8, cross section: 0.2 mm² - 2.5 mm², AWG: 24-12, mounting type: wire to wire or wire to board



Approvals



General Information

Product Name	DPSC5.08WW-4W
Connection Method	Spring Cage Connection
Rating	250 V / 16 A / 2.5 mm ² / Nm
HSN Number	85389000
Standard Packing Qty (in No)	50
Country Of Origin	India
Screw thread	NAV

Dimensions & Weight

Width	36.26 mm	1.43 inch
Length	45.25 mm	1.78 inch
Height	14.5 mm	0.57 inch
Weight of std. Packing Unit	1 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	0.2 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.2 mm ²
Conductor cross section solid max	2.5 mm ²

Rated Conductor Size

Conductor cross section flexible min	0.2 mm ²
Conductor cross section flexible max	2.5 mm ²

Conductor cross section solid min	0.2 mm ²
Conductor cross section solid max	2.5 mm ²

Ratings - UL


UL Standard	UL 1059
B - UL Nominal Voltage U _N	300 V
B - UL Nominal Current I _N	16 A
B - UL Wire Min	24 AWG
B - UL Wire Max	12 AWG

Product Accessories

Marker For Terminal Blocks

LABEL KN5.08	Pitch : 5.08 mm	
--------------	-----------------	---

Tool

DPSCCOT	Height : 6.90 mm Width : 5.00 mm Length : 20.30 mm	
---------	--	---