



## DPSC7.50PM-4W

Terminal Type - DPSC7.50PM - 4W , Plug & socket type terminal block , nominal voltage: 400 V, nominal current: 16 A, connection method: Spring cage connection , number of connections: 8, Rated cross section: 2.5 mm<sup>2</sup>, cross section: 0.2 mm<sup>2</sup> - 2.5 mm<sup>2</sup>, AWG : 24-12 , mounting type: Panel mounting / Surface mounting



### Approvals



### General Information

Product Name	DPSC7.50PM-4W
Connection Method	Spring Cage Connection
Rating	400 V / 16 A / 2.5 mm <sup>2</sup> / Nm
HSN Number	8904476703293
Standard Packing Qty (in No)	50
Country Of Origin	India
Screw thread	NAV

### Dimensions & Weight

Width	43 mm	1.69 inch
Length	45 mm	1.77 inch
Height	14.5 mm	0.57 inch
Weight of std. Packing Unit	1.03 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

### Rated Conductor Size

Conductor cross section flexible min	0.2 mm <sup>2</sup>
Conductor cross section flexible max	2.5 mm <sup>2</sup>
Conductor cross section solid min	0.2 mm <sup>2</sup>
Conductor cross section solid max	2.5 mm <sup>2</sup>

### Rated Conductor Size

Conductor cross section flexible min	0.2 mm <sup>2</sup>
Conductor cross section flexible max	2.5 mm <sup>2</sup>

Conductor cross section solid min	0.2 mm <sup>2</sup>
Conductor cross section solid max	2.5 mm <sup>2</sup>

**Ratings - UL**

UL Standard	UL 1059
B - UL Nominal Voltage U <sub>N</sub>	300 V
B - UL Nominal Current I <sub>N</sub>	16 A
B - UL Wire Min	24 AWG
B - UL Wire Max	12 AWG

**Product Accessories**

**Marker For Terminal Blocks**

LABEL KN7.5	Height : 1.60 mm Pitch : 7.50 mm Length : 3.40 mm	
-------------	---	---

**Tool**

DPSCCOT	Height : 6.90 mm Width : 5.00 mm Length : 20.30 mm	
---------	--	---

