DPSC7.50PM-4W

Terminal Type - DPSC7.50PM - 4W , Plug & socket type terminal block , nominal voltage: 400 V, nominal current: 16 A, connection method: Spring cage connection , number of connections: 8, Rated cross section: 2.5 mm², cross section: 0.2 mm² - 2.5 mm², AWG : 24-12 , mounting type: Panel mounting / Surface mounting





Approvals

General Information

Product Name	DPSC7.50PM-4W
Connection Method	Spring Cage Connection
Rating	400 V / 16 A / 2.5 mm^2 / Nm
HSN Number	85389000
Standard Packing Qty (in No)	50
Country Of Origin	India
Screw thread	NAV

Dimensions & Weight

Width	43 mm	1.69 inch
Length	45 mm	1.77 inch
Height	14.5 mm	0.57 inch
Weight of std. Packing Unit	1.03 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khaki

Rated Conductor Size

Conductor cross section flexible min	0.2 mm^2
Conductor cross section flexible max	2.5 mm^2
Conductor cross section solid min	0.2 mm^2
Conductor cross section solid max	2.5 mm^2

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U_N	300 V

B - UL Nominal Current I_N	16 A
B - UL Wire Min	24 AWG
B - UL Wire Max	12 AWG

Product Accessories

Marker For Terminal Blocks		
LABEL KN7.5	Height : 1.60 mm Width : 7.50 mm Length : 3.40 mm	

Tool		
DPSCCOT	Height : 6.90 mm Width : 5.00 mm Length : 20.30 mm	