



DPSC7.50PM-6W

Terminal Type - DPSC7.50PM - 6W , Plug & socket type terminal block , nominal voltage: 400 V, nominal current: 16 A, connection method: Spring cage connection , number of connections: 12, Rated cross section: 2.5 mm², cross section: 0.2 mm² - 2.5 mm², AWG : 24-12 , mounting type: Panel mounting / Surface mounting



Approvals



General Information

| | |
|------------------------------|---|
| Product Name | DPSC7.50PM-6W |
| Connection Method | Spring Cage Connection |
| Rating | 400 V / 16 A / 2.5 mm ² / Nm |
| HSN Number | 8904476703286 |
| Standard Packing Qty (in No) | 50 |
| Country Of Origin | India |
| Screw thread | NAV |

Dimensions & Weight

| | | |
|-----------------------------|----------|-----------|
| Width | 58 mm | 2.28 inch |
| Length | 45 mm | 1.77 inch |
| Height | 14.45 mm | 0.57 inch |
| Weight of std. Packing Unit | 1.43 Kg | |

Material Data

| | |
|---------------------|---|
| Insulating Material | Polyamide 6,6 |
| Standard Colour | Gray |
| Colour Variants | Red, Yellow, Blue, Black, Green, Khakhi |

Rated Conductor Size

| | |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 0.2 mm ² |
| Conductor cross section flexible max | 2.5 mm ² |
| Conductor cross section solid min | 0.2 mm ² |
| Conductor cross section solid max | 2.5 mm ² |

Rated Conductor Size

| | |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 0.2 mm ² |
| Conductor cross section flexible max | 2.5 mm ² |

| | |
|-----------------------------------|---------------------|
| Conductor cross section solid min | 0.2 mm ² |
| Conductor cross section solid max | 2.5 mm ² |

Ratings - UL

| | |
|---------------------------------------|---------|
| UL Standard | UL 1059 |
| B - UL Nominal Voltage U _N | 300 V |
| B - UL Nominal Current I _N | 16 A |
| B - UL Wire Min | 24 AWG |
| B - UL Wire Max | 12 AWG |

Product Accessories

Marker For Terminal Blocks

| | | |
|-------------|---|---|
| LABEL KN7.5 | Height : 1.60 mm Pitch : 7.50 mm Length : 3.40 mm |  |
|-------------|---|---|

Tool

| | | |
|---------|--|---|
| DPSCCOT | Height : 6.90 mm Width : 5.00 mm Length : 20.30 mm |  |
|---------|--|---|

