



## DSDT2.5

Terminal Type - DSDT2.5, Disconnecting terminal block, nominal voltage: 1000 V, nominal current: 17.5 A, Rated cross-section – 2.5 mm<sup>2</sup>, connection method: Spring clamp connection, number of connections: 2, cross-section: 0.5 mm<sup>2</sup> - 2.5 mm<sup>2</sup>, AWG: 22-14 , mounting type: TS 35/7.5, TS 35/15



### Approvals



### General Information

Product Name	DSDT2.5
Connection Method	Spring Cage Connection
Rating	1000 V / 17.5 A / 2.5 mm <sup>2</sup>
HSN Number	85389000
Standard Packing Qty (in No)	100
Country Of Origin	India
Screw thread	NA

### Dimensions & Weight

Width	5 mm	0.2 inch
Length	70 mm	2.76 inch
Height	37.5 mm	1.48 inch
Weight of std. Packing Unit	1.2 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

### Rated Conductor Size

Conductor cross section flexible min	0.5 mm <sup>2</sup>
Conductor cross section flexible max	2.5 mm <sup>2</sup>
Conductor cross section solid min	0.5 mm <sup>2</sup>
Conductor cross section solid max	2.5 mm <sup>2</sup>

### Rated Conductor Size

Conductor cross section flexible min	0.5 mm <sup>2</sup>
Conductor cross section flexible max	2.5 mm <sup>2</sup>

Conductor cross section solid min	0.5 mm <sup>2</sup>
Conductor cross section solid max	2.5 mm <sup>2</sup>

### Ratings - CSA


CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage U <sub>N</sub>	600 V
B - CSA Nominal Current I <sub>N</sub>	15 A
B - CSA Wire Min	22 AWG
B - CSA Wire Max	14 AWG



### Ratings - UL

UL Standard	
B - UL Nominal Voltage U <sub>N</sub>	0 V
B - UL Nominal Current I <sub>N</sub>	0 A
B - UL Wire Min	AWG
B - UL Wire Max	AWG

### Product Accessories

Cover Profile		
PCPDBF-3	Height : 14.10 mm Thickness : 1.50 mm Length : 79.00 mm	

DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

<b>End Clamp</b>		
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
<b>End Cover</b>		
DPDT2.5	Height : 23.00 mm Width : 2.00 mm Length : 60.00 mm	
<b>Marker For Terminal Blocks</b>		
LABEL KN5	Height : 2.42 mm Width : 5.00 mm Length : 7.50 mm	

Partition Plate		
DBF-3	Height : 50.00 mm Width : 3.00 mm Length : 78.00 mm	
Plug-in Bridge/Jumper		
SSL2.5	Height : 22.80 mm Width : 4.85 mm Pitch : 3.20 mm Length : 8.40 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	