



## DSET2.5-1x2

Terminal Type - DSET2.5-1X2, Multi-Conductor Ground modular terminal block, connection method: Spring Cage connection, number of connections: 3, Rated cross-section- 2.5 mm<sup>2</sup>, cross-section: 0.5 mm<sup>2</sup> - 2.5 mm<sup>2</sup>, mounting type: TS 35/7.5, TS 35/15



### Approvals



### General Information

|                              |                        |
|------------------------------|------------------------|
| Product Name                 | DSET2.5-1x2            |
| Connection Method            | Spring Cage Connection |
| Rating                       | 2.5 mm <sup>2</sup>    |
| HSN Number                   | 85389000               |
| Standard Packing Qty (in No) | 100                    |
| Country Of Origin            | India                  |
| Screw thread                 | NA                     |

### Dimensions & Weight

|                             |         |           |
|-----------------------------|---------|-----------|
| Width                       | 5 mm    | 0.2 inch  |
| Length                      | 66.5 mm | 2.62 inch |
| Height                      | 34.3 mm | 1.35 inch |
| Weight of std. Packing Unit | 1.25 Kg |           |

### Material Data

|                     |               |
|---------------------|---------------|
| Insulating Material | Polyamide 6,6 |
| Standard Colour     | Green-Yellow  |
| Colour Variants     | -             |

### Rated Conductor Size








|                                      |                     |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 0.5 mm <sup>2</sup> |
| Conductor cross section flexible max | 2.5 mm <sup>2</sup> |
| Conductor cross section solid min    | 0.5 mm <sup>2</sup> |
| Conductor cross section solid max    | 2.5 mm <sup>2</sup> |









### Rated Conductor Size


|                                      |                     |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 0.5 mm <sup>2</sup> |
| Conductor cross section flexible max | 2.5 mm <sup>2</sup> |
| Conductor cross section solid min    | 0.5 mm <sup>2</sup> |

|                                   |                     |
|-----------------------------------|---------------------|
| Conductor cross section solid max | 2.5 mm <sup>2</sup> |
|-----------------------------------|---------------------|

## Product Accessories

| Cover Profile          |                                                                                      |                                                                                       |
|------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| PCPDBF-3               | Height : 14.10 mm<br>Thickness : 1.50 mm<br>Length : 79.00 mm                        |    |
| DIN Rail Perforated    |                                                                                      |                                                                                       |
| CHKDS                  | Height : 15.00 mm<br>Width : 35.00 mm<br>Thickness : 1.50 mm<br>Length : 2,000.00 mm |    |
| CHKS                   | Height : 7.50 mm<br>Width : 35.00 mm<br>Thickness : 1.00 mm                          |    |
| DIN Rail, Unperforated |                                                                                      |                                                                                       |
| CHKD                   | Height : 15.00 mm<br>Width : 35.00 mm<br>Thickness : 1.50 mm                         |   |
| CHK                    | Height : 7.50 mm<br>Width : 35.00 mm<br>Thickness : 1.00 mm                          |  |
| End Cap                |                                                                                      |                                                                                       |
| CHKENDCAP              | Height : 14.00 mm<br>Width : 9.00 mm<br>Length : 41.50 mm                            |  |
| End Clamp              |                                                                                      |                                                                                       |
| SCUP                   | Height : 34.00 mm<br>Width : 9.00 mm<br>Length : 44.75 mm                            |  |
| SCEC35                 | Height : 31.50 mm<br>Width : 8.00 mm<br>Length : 45.80 mm                            |  |
| SCUSL                  | Height : 41.10 mm<br>Width : 8.00 mm<br>Length : 47.50 mm                            |  |

| End Clamp                  |                                                            |                                                                                       |
|----------------------------|------------------------------------------------------------|---------------------------------------------------------------------------------------|
| SCUDD                      | Height : 50.00 mm<br>Width : 10.00 mm<br>Length : 55.60 mm |    |
| DCKN                       | Height : 33.00 mm<br>Width : 6.00 mm<br>Length : 43.50 mm  |    |
| DCKN10                     | Height : 35.00 mm<br>Width : 10.00 mm<br>Length : 43.50 mm |    |
| SCKN                       | Height : 34.50 mm<br>Width : 8.00 mm<br>Length : 44.90 mm  |    |
| SCUN                       | Height : 35.50 mm<br>Width : 9.50 mm<br>Length : 50.60 mm  |   |
| End Cover                  |                                                            |                                                                                       |
| DSMP2.5-1x2                | Height : 26.50 mm<br>Width : 2.50 mm<br>Length : 66.00 mm  |  |
| Marker For Terminal Blocks |                                                            |                                                                                       |
| LABEL KN5                  | Height : 2.42 mm<br>Width : 5.00 mm<br>Length : 7.50 mm    |  |
| Partition Plate            |                                                            |                                                                                       |
| DBF-3                      | Height : 50.00 mm<br>Width : 3.00 mm<br>Length : 78.00 mm  |  |
| Marker carriers            |                                                            |                                                                                       |
| SCUDDMLH                   | Height : 71.50 mm<br>Width : 11.00 mm<br>Length : 55.60 mm |  |
| SCUNMLH                    | Height : 53.50 mm<br>Width : 11.00 mm<br>Length : 50.60 mm |  |

| Marker carriers |                                                            |                                                                                     |
|-----------------|------------------------------------------------------------|-------------------------------------------------------------------------------------|
| DCKNMLH         | Height : 45.00 mm<br>Width : 10.00 mm<br>Length : 43.50 mm |  |
| SCKNMLH         | Height : 42.00 mm<br>Width : 16.00 mm<br>Length : 44.70 mm |  |

