


## DST10-1X2

Terminal Type - DST10-1X2 , Multi-Conductor terminal block, nominal voltage: 1000 V, nominal current: 57 A, Rated cross-section - 10 mm<sup>2</sup>, connection method: Spring clamp connection, number of connections: 3, cross-section: 1.5 mm<sup>2</sup> - 10 mm<sup>2</sup>, mounting type: TS 35/7.5, TS 35/15



### Approvals



### General Information

Product Name	DST10-1X2
Connection Method	Spring Cage Connection
Rating	1000 V / 57 A / 10 mm <sup>2</sup>
HSN Number	85389000
Standard Packing Qty (in No)	50
Country Of Origin	India
Screw thread	-

### Dimensions & Weight

Width	10 mm	0.39 inch
Length	97.5 mm	3.84 inch
Height	42 mm	1.65 inch
Weight of std. Packing Unit	1.75 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi, Gray

### Rated Conductor Size

Conductor cross section flexible min	1.5 mm <sup>2</sup>
Conductor cross section flexible max	10 mm <sup>2</sup>
Conductor cross section solid min	1.5 mm <sup>2</sup>
Conductor cross section solid max	10 mm <sup>2</sup>

### Rated Conductor Size

Conductor cross section flexible min	1.5 mm <sup>2</sup>
Conductor cross section flexible max	10 mm <sup>2</sup>

Conductor cross section solid min	1.5 mm <sup>2</sup>
Conductor cross section solid max	10 mm <sup>2</sup>


**Product Accessories**

**Cover Profile**


PCPDBF-5	Height : 14.10 mm Thickness : 1.50 mm Length : 113.00 mm	
----------	--	---


**DIN Rail Perforated**

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
-------	--	---

CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
------	---	---

**DIN Rail, Unperforated**

CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
------	--	---

CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
-----	---	---

**End Cap**

CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
-----------	---	---

**End Clamp**

SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
------	---	---

SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
--------	---	---

SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
-------	---	---

<b>End Clamp</b>		
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
<b>End Cover</b>		
DSMP10-1x2	Height : 34.00 mm Width : 2.00 mm Length : 97.50 mm	
<b>Marker For Terminal Blocks</b>		
LABEL KN10	Height : 2.89 mm Width : 10.00 mm Length : 8.50 mm	
<b>Partition Plate</b>		
DBF-5	Height : 54.00 mm Width : 3.00 mm Length : 112.00 mm	
<b>Plug-in Bridge/Jumper</b>		
SSL10	Height : 25.60 mm Width : 9.40 mm Pitch : 5.95 mm Length : 9.00 mm	
<b>Marker carriers</b>		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	

Marker carriers		
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	