


## DST10-1X2

Terminal Type - DST10-1X2, Multi-Conductor terminal block, nominal voltage: 1000 V, nominal current: 57 A, Rated cross-section - 10 mm<sup>2</sup>, connection method: Spring clamp connection, number of connections: 3, cross-section: 1.5 mm<sup>2</sup> - 10 mm<sup>2</sup>, mounting type: TS 35/7.5, TS 35/15



### Approvals



### General Information

|                              |                                    |
|------------------------------|------------------------------------|
| Product Name                 | DST10-1X2                          |
| Connection Method            | Spring Cage Connection             |
| Rating                       | 1000 V / 57 A / 10 mm <sup>2</sup> |
| HSN Number                   | 85389000                           |
| Standard Packing Qty (in No) | 50                                 |
| Country Of Origin            | India                              |
| Screw thread                 | -                                  |

### Dimensions & Weight

|                             |         |           |
|-----------------------------|---------|-----------|
| Width                       | 10 mm   | 0.39 inch |
| Length                      | 97.5 mm | 3.84 inch |
| Height                      | 42 mm   | 1.65 inch |
| Weight of std. Packing Unit | 1.75 Kg |           |








### Material Data









|                     |                                              |
|---------------------|----------------------------------------------|
| Insulating Material | Polyamide 6,6                                |
| Standard Colour     | Gray                                         |
| Colour Variants     | Red, Yellow, Blue, Black, Green, Khaki, Grey |


### Rated Conductor Size

|                                      |                     |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 1.5 mm <sup>2</sup> |
| Conductor cross section flexible max | 10 mm <sup>2</sup>  |
| Conductor cross section solid min    | 1.5 mm <sup>2</sup> |
| Conductor cross section solid max    | 10 mm <sup>2</sup>  |

### Product Accessories

| Cover Profile          |                                                                                      |                                                                                       |
|------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| PCPDBF-5               | Height : 14.10 mm<br>Thickness : 1.50 mm<br>Length : 113.00 mm                       |    |
| DIN Rail Perforated    |                                                                                      |                                                                                       |
| CHKDS                  | Height : 15.00 mm<br>Width : 35.00 mm<br>Thickness : 1.50 mm<br>Length : 2,000.00 mm |    |
| CHKS                   | Height : 7.50 mm<br>Width : 35.00 mm<br>Thickness : 1.00 mm                          |    |
| DIN Rail, Unperforated |                                                                                      |                                                                                       |
| CHKD                   | Height : 15.00 mm<br>Width : 35.00 mm<br>Thickness : 1.50 mm                         |    |
| CHK                    | Height : 7.50 mm<br>Width : 35.00 mm<br>Thickness : 1.00 mm                          |   |
| End Cap                |                                                                                      |                                                                                       |
| CHKENDCAP              | Height : 14.00 mm<br>Width : 9.00 mm<br>Length : 41.50 mm                            |  |
| End Clamp              |                                                                                      |                                                                                       |
| SCUP                   | Height : 34.00 mm<br>Width : 9.00 mm<br>Length : 44.75 mm                            |  |
| SCEC35                 | Height : 31.50 mm<br>Width : 8.00 mm<br>Length : 45.80 mm                            |  |
| SCUSL                  | Height : 41.10 mm<br>Width : 8.00 mm<br>Length : 47.50 mm                            |  |
| SCUDD                  | Height : 50.00 mm<br>Width : 10.00 mm<br>Length : 55.60 mm                           |  |

| End Clamp                  |                                                                             |                                                                                       |
|----------------------------|-----------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| DCKN                       | Height : 33.00 mm<br>Width : 6.00 mm<br>Length : 43.50 mm                   |    |
| DCKN10                     | Height : 35.00 mm<br>Width : 10.00 mm<br>Length : 43.50 mm                  |    |
| SCKN                       | Height : 34.50 mm<br>Width : 8.00 mm<br>Length : 44.90 mm                   |    |
| SCUN                       | Height : 35.50 mm<br>Width : 9.50 mm<br>Length : 50.60 mm                   |    |
| End Cover                  |                                                                             |                                                                                       |
| DSMP10-1x2                 | Height : 34.00 mm<br>Width : 2.00 mm<br>Length : 97.50 mm                   |   |
| Marker For Terminal Blocks |                                                                             |                                                                                       |
| LABEL KN10                 | Height : 2.89 mm<br>Width : 10.00 mm<br>Length : 8.50 mm                    |  |
| Partition Plate            |                                                                             |                                                                                       |
| DBF-5                      | Height : 54.00 mm<br>Width : 3.00 mm<br>Length : 112.00 mm                  |  |
| Plug-in Bridge/Jumper      |                                                                             |                                                                                       |
| SSL10                      | Height : 25.60 mm<br>Width : 9.40 mm<br>Pitch : 5.95 mm<br>Length : 9.00 mm |  |
| Marker carriers            |                                                                             |                                                                                       |
| SCUDDMLH                   | Height : 71.50 mm<br>Width : 11.00 mm<br>Length : 55.60 mm                  |  |
| SCUNMLH                    | Height : 53.50 mm<br>Width : 11.00 mm<br>Length : 50.60 mm                  |  |

| Marker carriers |                                                            |                                                                                     |
|-----------------|------------------------------------------------------------|-------------------------------------------------------------------------------------|
| DCKNMLH         | Height : 45.00 mm<br>Width : 10.00 mm<br>Length : 43.50 mm |  |
| SCKNMLH         | Height : 42.00 mm<br>Width : 16.00 mm<br>Length : 44.70 mm |  |

